GENERIC SCOPE OF WORK BASIC CONTRACT

CONTRACT TYPE

□ Specific Rate of Pay

☑ Cost Plus Fixed Fee

□ Other

SOW DATE: April 7, 2023

PROJECT NUMBER: PM 0253-299

PROJECT LOCATION: I-25 (025A) US 36 to 104th Avenue (M.P. 216.520 to M.P. 221.450)

PROJECT CODE: 25563

THE COMPLETE SCOPE OF WORK INCLUDES THIS DOCUMENT (ATTACHED TO THE CONTRACT FOR CONSULTANT SERVICES)

SECTION 1 PROJECT SPECIFIC INFORMATION

SECTION 2 PROJECT MANAGEMENT AND COORDINATION

SECTION 3 EXISTING FEATURES

SECTION 4 GENERAL INFORMATION

SECTION 5 PROJECT INITIATION AND CONTINUING REQUIREMENTS

SECTION 6 NEPA ENVIRONMENTAL WORK TASK DESCRIPTIONS

SECTION 7 PRECONSTRUCTION WORK TASK DESCRIPTIONS

SECTION 8 SERVICES AFTER DESIGN

SECTION 9 CONTRACT CONCLUSION (CHECKLIST)

APPENDICES

Comments regarding this scope may be directed to:

CONTRACTS AND MARKET ANALYSIS BRANCH

Engineering Contracts Unit

Marci Gray, Contracting Officer 303-757-9297

TABLE OF CONTENTS

SECT		Page 5
	ECT SPECIFIC INFORMATION	3
	ION 2	11
	ECT MANAGEMENT AND COORDINATION	
	ION 3	12
EXIST	ΓING FEATURES	
SECT	ION 4	13
GENE	ERAL INFORMATION	
SECT	ION 5	16
PROJ	ECT INITIATION AND CONTINUING REQUIREMENTS	
A.	PROJECT MEETINGS	16
B.	PROJECT MANAGEMENT	18
C.	DEVELOP A PROJECT SCHEDULE AND ASSIGN TASKS	18
D.	QUALITY ASSURANCE/QUALITY CONTROL (QA/QC)	18
E.	VALUE ENGINEERING (VE) STUDY	18
F.	OBTAIN NECESSARY RIGHT-OF-ENTRY AND PERMITS	19
G.	PROJECT CHARTER	19
H.	OTHER PROCESS SUPPORT	20
SECT	ION 6	21
ENVI	RONMENTAL WORK TASK DESCRIPTIONS	
A.	PROJECT INITIATION	21
B.	ENVIRONMENTAL ANALYSIS AND DOCUMENTATION	22
C.	COST ESTIMATES AND FINANCIAL ANALYSIS	23
D.	DATA COLLECTION, FIELD INVESTIGATION, MITIGATION MEASURES, AND DELIVERABL	23
E.	DELIVERABLES	35
F.	PUBLIC AND AGENCY INVOLVEMENT	36
G.	NEPA DOCUMENTATION PROCESS	37
SECT	ION 7	40
PREC	ONSTRUCTION WORK TASK DESCRIPTIONS	
A.	PROJECT INITIATION AND CONTINUING REQUIREMENTS	40
B.	PROJECT DEVELOPMENT	41
C.	PRELIMINARY DESIGN	43
D.	FINAL DESIGN	55
E.	COMMUNICATIONS	61
F.	PRIOR TO AD	61

G.	CORRIDOR MANAGEMENT SUPPORT	64
SECT	ION 8	66
SERV	ICES AFTER DESIGN	
A.	REVIEW OF SHOP DRAWINGS	66
В.	CONSTRUCTION SERVICES	66
C.	POST DESIGN PLAN MODIFICATIONS	67
D.	POST CONSTRUCTION SERVICES	67
SECT	ION 9	70
CONT	TRACT CONCLUSION (CHECKLIST)	

APPENDICES

APPENDIX A	REFERENCES
APPENDIX B	SPECIFIC DESIGN CRITERIA
APPENDIX C	DEFINITIONS

INSTRUCTIONS

Note:

This Scope of Work is to serve as a template for the Colorado Department of Transportation (CDOT) to develop and negotiate solid contracts with Consultant teams on projects and tasks. The Consultant shall coordinate all activities, tasks, meetings, communications and deliverables with the CDOT/Project Manager (PM) (or his or her designee) for this project. All submittals will be through the CDOT/PM or a designee, who will make appropriate distribution. Upon notice to proceed, the Consultant shall be responsible and will account for all effort contained in the Final Scope of Work.

This Draft Scope of Work has been reviewed by the Department and reflects a plan of approach based on the known goals. One factor determining the selection of a Consultant is the ability of that Consultant to analyze the project goals, evaluate the work elements, and formulate a work plan. This process may produce new approaches or modification to the project work elements. Because of that, all Consultants should be aware that the Final Scope of Work for a project will be produced with input from the selected Consultant.

SECTION 1 PROJECT SPECIFIC INFORMATION

1. PROJECT BACKGROUND

I-25 in the North Denver Metro Region is an important North/South thoroughfare connecting people with Colorado's abundant, diverse, critical and cultural resources. This corridor is vital to the efficient movement of people, goods, and services to and from the Denver Metro Region and Northern Colorado. CDOT is seeking Environmental and Design Services to prepare and advertise a full PS&E package for construction to improve the I-25 corridor from approximately US 36 to 104th Avenue. Currently, CDOT is conducting an initial Transit Impact and Safety Analysis Design Alternative study. A number of multi-modal alternatives are expected to be generated as a result of this study as described below.

Additionally, this project shall build upon prior studies along the corridor which are described at a high level below with links to the actual reports:

- 1. 21180 EA Validation & Supplemental Options White Paper Link
- 2. 24962 Safety & Transit Impacts Analysis White Paper Link

In 2011, CDOT completed the *North I-25 Final Environmental Impact Statement, Final Section 4(f) Evaluation* (FEIS) (2011 North I-25 Final EIS, Final 4(f) Evaluations, North I-25 Record of Decision), *North I-25 Record of Decision 1* (ROD1). The FEIS identified and evaluated multimodal transportation improvements along the 61-mile I-25 transportation corridor extending from the Fort Collins/Wellington area to Denver. Between US 36 and 104th Avenue, the elements of the ROD1 Preferred Alternative that have been constructed include:

- Six 12-ft general-purpose lanes (three in each direction),
- Two 12-ft Express Lanes (one in each direction),
- A concrete barrier between the northbound and southbound directions of the roadway,
- Tolling and intelligent transportation system infrastructure, and
- Four new noise walls and the rehabilitation of existing noise walls.
- The elements of the ROD1 Preferred Alternative that have not been constructed include:
 - A 4-ft buffer along the inside travel lane between the Express Lane and general-purpose lane (one
 in each direction),
 - o 12-ft inside and outside shoulders in each direction, and
 - Replacement of the 88th Avenue bridge over I-25.

CDOT completed the *North I-25, US 36 to SH 7 Planning and Environmental Linkages (PEL) study* in 2014 (2014 North I-25, US 36 to SH 7 Planning and Environmental Linkages (PEL) Study). The *North I-25, US 36 to SH 7 PEL study* evaluated improvements to reduce congestion and improve safety on I-25 between US 36 and Colorado State Highway 7 (CO 7) by implementing near term, multimodal, and cost-effective transportation improvements that were compatible with long-term options and the recently constructed interchange structures along the corridor, including the I-25/84th Avenue interchange.

Within the project area the PEL Recommended Alternative included:

- Adding a fourth 12-ft general-purpose lane in each direction from 84th Avenue to Thornton Parkway;
- Constructing 12-ft continuous acceleration and deceleration auxiliary lanes between the I-25/104th Avenue interchange and the I-25/Thornton Parkway interchange; and
- Reconstructing the Thornton Park-n-Ride to include an I-25 median transit station accessed by an above-ground pedestrian bridge.

In 2017, FHWA, in conjunction with CDOT and local agencies, completed the *I-25 North Metro Managed Lanes Road Safety Audit (RSA) Report* (available for review), which evaluated conditions along and

identified safety enhancements for the I-25 corridor from US 36 to 112th Avenue. CDOT has implemented many of the safety enhancements recommended in the 2017 RSA. The implemented safety enhancements include educational outreach, enhanced law enforcement, and several roadway maintenance and engineering improvements. Roadway improvements have included signing and striping improvements, the implementation of queue warning systems, the addition of shoulder pull-out areas in select locations, rumble strips, and on-ramp modifications.

Subsequent to the EIS and PEL, CDOT initiated analysis of the corridor through an un-published Environmental Assessment (EA). This EA evaluated the previously analyzed and recommended transportation improvements. Due to fiscal constraint, amongst other challenges, this EA was not completed. However, the study area for this contract is similar to the prior EA with some of the prior analysis being relevant. Those areas with relevant analysis are notated throughout this Scope of Work.

Additional items:

- 2012 North Metro Managed Lanes Extension and Express Bus Project
- Former and non published I-25 (US 36 to 104th) Environmental Assessment Technical Reports
- 2023 (anticipated publication date) I-25 Transit Impact and Safety Analysis Design Alternative Study
- 2045 Statewide Transit Plan

2. PROJECT GOALS

A. System Functionality

- a. Produce a project that is consistent with the vision and commitments in place from surrounding planning and studies.
- b. Deliver a project that is consistent with and building upon other CDOT endeavors including system management, corridor management, and technology initiatives.
- B. Improved safety Improve the safety of all travelers in the corridor by fully supporting CDOT's strategy. Whole System. Whole Safety. *Bringing everyone home safely*.
- C. Schedule Align with CDOT's 10-year plan to construct improvements by FY27, incorporate previous planning efforts for I-25 Segment 2, and accelerate environmental processes to quickly obtain a NEPA decision document.

D. Environmental

- a. Adhere to all environmental compliance requirements and regulations.
- b. Implement innovative methods for environmental stewardship and community supported enhancements within the project scope, schedule, and budget

E. Communication

a. Develop and execute a thoughtful and efficient communication plan showing how and when the stakeholders and public will be engaged in a manner that is effective and meets NEPA requirements.

In achieving these project goals, this project is intended to:

- 1. Replace functionally obsolete bridge at 88th Ave
- 2. Improve safety in corridor
- 3. Improve I-25 traffic operations
- 4. Improve the existing transit experience at Thornton Park-n-Ride in addition to a potential pedestrian underpass or overpass.
- 5. Improve conveyance for the Niver Creek and tributary floodplain and unimproved detention in CDOT

ROW.

- 6. Designing not to preclude and to potentially accommodate in the future:
 - i. Express lane direct connects from I-270

While considering:

- A. Aesthetic and context-sensitive design
- B. Pedestrian and bicycle connectivity, both across the corridor and interfacing with existing features, developing a safe walkable and bikeable experience in the area.
- C. Freight access and considerations

The Consultant shall deliver a project that is consistent with and builds upon other CDOT endeavors, including system management, corridor management, and technology initiatives. The project must conform to the vision and commitments in place from previous and ongoing projects within the project area.

The work includes preliminary design, NEPA environmental process and final design. Accurate, meaningful, organized, and timely public communication to the public is essential.

This project is intended to produce the following improvements:

A.	Increased Capacity and Mobility Choice	\checkmark
B.	Improved Safety	\checkmark
C.	Higher Level-of-Service	V
D.	Improved Riding Surface (smoother or stronger pavement)	
E.	Bridge Replacement	V
F.	Resurfacing, Restoration, Rehabilitation	
G.	Reconstruction	\checkmark
Н.	Other	П

3. PROJECT LIMITS

This project is located on I-25 (025A), between milepost 216.520 and milepost 221.450 in Adams County.

4. PROJECT COSTS

The overall construction costs of this project have not been fully determined. CDOT's 10 year Plan has identified \$110M of Strategic Funding for both Design & Construction. Other funding sources will be needed but it is currently estimated at ~\$300,000,000.

5. WORK DURATION

The time for the work described in this scope is anticipated as approximately:

- NEPA 18 Months
- DECISION DOCUMENTATION 3 Months
- DESIGN AND RIGHT-OF-WAY 18 to 24 Months
- CONSTRUCTION (DESIGN SERVICES DURING CONSTRUCTION) 2 Years

6. CONSULTANT RESPONSIBILITY AND DUTIES

The Consultant is responsible for:

All Pre-Construction Tasks to Complete NEPA, Preliminary Design, Final Design, Right-of-Way, PS&E Preparation, Project Advertisement, and Design Services During and After Construction.

Currently, CDOT is conducting an initial 24962 Transit Impact and Safety Analysis Design Alternative Study to generate multimodal improvement alternatives that will move forward for further analysis and consideration. The selected firm will utilize the given alternatives, refine alternatives, and determine a preferred alternative. It is anticipated that the selected firm will then advance that alternative through the NEPA Clearance Process, Design and Construction.

Performance of the Consultant may be evaluated at each stage including the conclusion of the Environmental Phase. This scope of work and contract may be reevaluated once the preliminary EA process is complete and the lead agency has made a decision on how to proceed.

Consultant shall be available providing any and all pre-construction activities, documents, and deliverables needed to provide a safe, collaborative, and effective project regardless of if any specific scope items are listed herein.

7. WORK PRODUCT

The Consultant work products are:

A.	Reports (hard copy and/or digital, as required)	$\overline{\checkmark}$
B.	Geographic Information Systems (GIS) Data and Layers	$\overline{\checkmark}$
C.	Environmental Documents	
D.	Traffic Modeling Output	
E.	Field Inspection Review (FIR) Plans and Estimates	$\overline{\checkmark}$
F.	Final Office Review (FOR) Plans, Specifications, and Estimates	$\overline{\checkmark}$
G.	AD/Bid Plans, Specifications, Cost Estimate	\checkmark
H.	Construction Plan Package	\checkmark
I.	Project Coordination	\checkmark
J.	Schedules	\checkmark
K.	Meeting Minutes	
L.	Professional Engineer Stamped Record Sets	
M.	Design Support During Construction	

Requirements are further described in the sections that follow. All work required to complete this Scope of Work requires the use of English Units.

8. WORK PRODUCT COMPLETION

All submittals must be accepted by the CDOT Contract Administrator or designee. The Consultant work products are:

- A. Engineering reports, including traffic & safety, pavement design, geotechnical and structure selection reports.
- B. Subsurface utilities investigation
- C. Design survey data and property ownership information
- D. Interstate access request and 1601 process
- E. Environmental Assessment associated supporting technical reports, including a technical summary of the engineering and environmental considerations, assumptions, analysis methodologies, and graphic displays of the recommended alternative(s).
- F. National Environmental Policy Act decision document
- G. Field Inspection Review (FIR) plans, specifications and estimates
- H. Project coordination
- I. Project schedules
- J. Meeting minutes
- K. Public meeting materials
- L. Project delivery selection matrix support

Requirements are further described in the sections that follow. All work required to complete this work requires the use of English units.

9. ADDITIONAL PROJECT INFORMATION

Additional information regarding this project is included in the following documents:

- A. 21180 EA Validation & Supplemental Options White Paper
- B. North I-25 Final Environmental Impact Statement, Final Section 4(f) Evaluation (FEIS) (2011 North I-25 Final EIS, Final 4(f) Evaluations, North I-25 Record of Decision), North I-25 Record of Decision 1 (ROD1)
- C. North I-25, US 36 to SH 7 Planning and Environmental Linkages (PEL) study
- D. I-25 North Metro Managed Lanes Road Safety Audit (RSA) Report
- E. 2012 North Metro Managed Lanes Extension and Express Bus Project
- F. Former and non published I-25 (US 36 to 104th) Environmental Assessment Technical Reports
- G. 2045 Statewide Transit Plan
- H. 24962 Transit and Safety Impact Analysis Executive Summary

Copies of these documents may be requested from CDOT. A moderate fee may be required for copies.

SECTION 2 PROJECT MANAGEMENT AND COORDINATION

1. CDOT CONTACT

The Contract Administrator for this project is: Thomas Magenis, Region 1 Resident Engineer.

Active day-to-day administration of the contract will be delegated to the CDOT/PM:

A. Name: Casey Martinez
B. Title: Project Manager

C. Address: 4670 Holly Street, Denver, CO 80216

D. Office phone: 303-398-6743
E. Cell phone: 505-231-4687
F. Fax: 303-398-6781

2. PROJECT COORDINATION

Coordination will be required with the following:

- A. Cities: Northglenn & Thornton
- B. Counties: Adams County
- C. Irrigation Ditch Companies
- D. Regional Transportation District (RTD)
- E. Denver Regional Council of Governments (DRCOG)
- F. Metropolitan Planning Organizations (MPO's)
- G. U.S. Army Corps of Engineers (USACE)
- H. Mile High Flood District (MHFD)
- I. Federal Emergency Management Agency (FEMA)
- J. Colorado Division of Parks & Wildlife (CPW)
- K. Environmental Protection Agency (EPA)
- L. U.S. Fish and Wildlife Service (USFWS)
- M. Federal Highway Administration (FHWA)
- N. Federal Transit Authority (FTA)
- O. Utilities
- P. Colorado Department of Public Health and Environment (CDPHE),
- Q. Air Pollution Control Division (APCD) of CDPHE
- R. Colorado State Patrol
- S. Colorado State Historic Preservation Office (SHPO)
- T. Smart Commute Metro North Transportation Management Organization
- U. Commuting Solutions Transportation Management Organization

The consultant should anticipate that a design that affects another agency has to be accepted by that agency prior to its acceptance by CDOT. Submittals to affected agencies will be coordinated with CDOT.

SECTION 3 EXISTING FEATURES

Note: This Section lists known features in the area. It should not be considered as complete, and should include, as appropriate, information from Section 2 Project Management and Coordination. The Consultant should be alert to the existence of other possible conflicts.

1. STRUCTURES

MAJOR E-17-OD E-17-OC E-17-NZ E-17-PV E-17-NW E-17-OZ E-17-PU E-17-OO E-17-QA E-17-JK E-17-QJ E-17-FJ pedestrian underpass for potential replacement E-17-LE E-17-MJ E-17-ADP E-17-LN E-17-FI

MINOR

025A220770BL

025A220730BL

025A218935BL

025A218952BL

025A218680BL

025A216990BL

SIGN STRUCTURES Throughout

2. UTILITIES

Contact Utility Notification Center of Colorado (U.N.C.C.) at 1-800-922-1987 or 811

3. IRRIGATION DITCHES

5. PERMANENT WATER QUALITY (PWQ) CONTROL MEASURES

EXDB00193 built under project 18695. EXDB00360, EXDB00029 built under project 17535. TRSW00152, TRSW00120, TRSW00115, TRSW00089, TRSW00053 built under project 16170

6.	OTHER	

SECTION 4 GENERAL INFORMATION

1. NOTICE TO PROCEED

Work shall not commence until the written Notice-to-Proceed is issued by CDOT. Work may be required, night or day, and/or weekends, and/or holidays, and/or split shifts. CDOT must concur in time lost reports prior to the time lost delays being subtracted from time charges. Subject to CDOT prior approval, the time charged may exclude time lost for:

- A. Reviews and Approvals
- B. Response and Direction

2. PROJECT COORDINATION

- A. Routine Working Contact: Routine working contact shall be between the CDOT/PM and the Consultant Project Manager (C/PM) as defined in Appendix C.
- B. Project Manager Requirements: Each Project Manager shall provide the others with the following:
 - A written synopsis or copy of their respective contacts by telephone and in person with others.
 - 2. Copies of pertinent written communications.

3. ROUTINE REPORTING AND BILLING

The Consultant shall provide the following on a routine basis:

- A. Coordination: Coordination of all contract activities by the C/PM.
- B. Periodic Reports and Billings: The periodic reports and billings required by CDOT.
- C. General Reports and Submittals: In general, all reports and submittals must be approved by CDOT prior to their content being utilized in follow-up work effort.

4. PERSONNEL QUALIFICATIONS

The C/PM must be approved by the CDOT Contract Administrator. Certain tasks must be done by Licensed Professional Engineers (PE) or Professional Land Surveyors (PLS) who are registered with the Colorado State Board of Registration for Professional Engineers and Land Surveyors. National Institute for Certification in Engineering Technology (NICET) certification or other certifications may be required for project inspectors and testers.

All tasks assigned to the Consultant must be conducted by a person on the Consultant team that is qualified and has specific expertise in that task. The qualified person is a professional with the necessary education, certifications (including registrations and licenses), skills, experience, qualities, or attributes to complete a particular task. Design of any special project features must be directed, completed, and overseen by a professional engineer with significant experience in design of those special project features.

It is the intent of CDOT that all key personnel be engaged to perform their specialty for all services required by this contract, and that the Consultant's key personnel be retained for the life of this contract to the extent practicable and to the extent that such services maximize the quality of work hereunder.

If the Consultant or a subconsultant decides to replace any of its key personnel, the Consultant shall notify the Project Manager in writing of the desired change. No such changes shall be made until at least two qualified replacement candidates are recommended by the Consultant and a replacement is approved in writing by the Project Manager. The Project Manager's approval shall not be unreasonably withheld. Failure of the Consultant to comply with the requirements of this provision may be the basis for CDOT's termination of this contract.

The Project Manager shall respond to the Consultant's written notice regarding replacement of key personnel within fifteen working days after the Project Manager receives the list of proposed changes. If the Project Manager or its designated representative does not respond within that time, the listed changes shall be deemed to be approved.

If, during the term of the contract, the Project Manager determines that the performance of approved key personnel is not acceptable, he shall notify the Consultant and give the Consultant the time which the Project Manager considers reasonable to correct such performance. Thereafter he may require the Consultant to reassign or replace such key personnel. If the Project Manager notifies the Consultant that certain of their key personnel or the key personnel of a subconsultant should be replaced, the Consultant shall use its best efforts to replace such key personnel within a reasonable time, but not to exceed thirty calendar days from the date of the Project Manager's notice.

This contract requires that the prime firm or any member of its team be pre-qualified in the following disciplines for the entire length of the contract.

Acoustical engineering, Architecture, Bridge Design, Bridge Inspection, Civil Engineering, Electrical Engineering, Environmental Engineering, Geotechnical Engineering, Highway & Street Design, Hydrology and Hydraulics (including PWQ), Landscape Architecture (including Stormwater Management Plans [SWMP]), Management (Contract Admin),—Mechanical Engineering, Materials Testing, Sanitary Engineering, Soils Engineering, Structural Engineering, Surveying, Transportation Engineering, Traffic Engineering, Tunneling, and Water Quality (including PWQ and SWMP).

5. CDOT COMPUTER/SOFTWARE INFORMATION

The consultant shall utilize the most recent CDOT adopted software. The primary software used by CDOT is as follows:

A. Earthwork ORD

B. Traffic Microsimulation model software (ex. TransModeler or Vissim)
C. Drafting/CADD ORD w/CDOT's formatting, configurations & standards

D. Survey/photogrammetry ORD

E. Pavement Design AASHTOWare Pavement ME Design

F. Bridge check CDOT Staff Bridge software shall be used in either design or design G. Estimating Transport (an AASHTO sponsored software) as used by CDOT

H. Specifications Microsoft Word
I. Scheduling Microsoft Project

J. Water Quality Data ArcGIS

K. Geographic Information System (GIS) ArcGIS w/CDOT's geodatabase, formatting configurations & standards

6. COMPUTER DATA COMPATIBILITY

The data format for submitting design computer files shall be compatible with the latest version of the adopted CDOT software as of Notice to Proceed for the contract. The Consultant shall immediately notify the CDOT/PM if the firm is unable to produce the desired format for any reason and cease work until the problem is resolved. Refer to Section 8, Table 1 - Submittals, for additional information regarding current formats and the acceptable transmittal media.

7. PROJECT DESIGN DATA AND STANDARDS

A. General:

Appendix A provides a comprehensive list of state and federal reference material. However, Appendix A does not contain local agency reference material that may be pertinent to some projects. The consultant is responsible for obtaining and ensuring compliance with the most recent CDOT-adopted version of the listed references including standards and specifications, manuals, and software, or as directed by the CDOT/PM. Conflicts in criteria shall be resolved by the CDOT/PM.

B. Specific Design Criteria:

Appendix B is a list of specific project criteria. The list is comprehensive and may include items that are not required for tasks defined in this scope. The Consultant shall submit any proposed changes to the pertinent criteria to the CDOT/PM at one of the periodic progress meetings prior to initiating design.

C. Construction Materials/Methods:

The materials and methods specified for construction will be selected to minimize the initial construction and long-term maintenance cost to the State of Colorado. Non-typical construction materials and methods must be approved in writing by CDOT.

SECTION 5 PROJECT INITIATION AND CONTINUING REQUIREMENTS

Note: This list establishes the individual task responsibility. Those tasks identified as CDOT/Other should utilize an abbreviation system to indicate whether the task will be completed by CDOT or another agency (i.e. "C" for CDOT and abbreviations as provided below). The consultant shall maintain the ability to perform all work tasks that are indicated below by an 'X' in the consultant column, in accordance with the forms and conditions contained herein, and the applicable CDOT standards. Where appropriate, mark "N/A" for not applicable items.

*Other Agency Abbreviations:

	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A p pl ic a bl
A. PROJECT MEETINGS			
The types and numbers of meetings shall be flexible and determined by an		v	
interactive process as approved by the CDOT/PM.		X	<u> </u>
1. Initial Project Kick-Off Meeting Schedule and facilitate initial project kick-off meeting. All appropriate disciplines should be included in the scoping meeting. Create an invitation list, send notices with a draft agenda prior to the meeting, and provide meeting minutes to all those invited. Whenever possible, the kick-off meeting will include an on-site inspection to familiarize the entire project team with the character and conditions of the area. The scoping meeting will also be used to clearly identify scope elements, responsibilities and coordination necessary to complete the work.	C	X	
2. Progress Meetings			
CDOT and Consultant team will meet periodically as required (typically every two weeks). The meetings will review activities required to be completed since the last meeting, problems encountered/anticipated and potential solutions, project schedule update, action items, and coordination required with other agencies.	С	X	
3. Public Meetings			
The Consultant shall provide the presentation aids, and help conduct the meeting. a. Small Group Meetings (one-on-one) Meet with property and business owners or others directly affected by the project work to identify likely impacts and discuss possible mitigation or resolutions.	C C	X X	
b. General Public Meetings (information and workshops) The format of these meetings will be dictated by the project and goals for the meetings. These meetings may be used to establish communications with the public, add to the "contact list", and gather information regarding local concerns. The meetings may also take the form of a work session or workshop with the affected parties.	C	X	
c. Public Review Meetings		X	

	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A p pl ic a bl
These meetings are intended to disseminate project progress information to			
the public and representatives of local entities. Notices will be mailed at least 14 days in advance of these meetings to those on the "contact list".			
4. Meeting Minutes			
Project meeting minutes shall be completed by the Consultant and provided to the CDOT/PM within one week of the actual meeting. When a definable task is discussed during a meeting, the minutes will identify the "Action Item", the party responsible for accomplishing it, and the proposed completion date.		X	
5. Contact List			
Establish and maintain a computerized list of all appropriate interested parties for	_		
the communication process.	С	X	
 a. The information on the list shall include as a minimum: b. Name 			
c. Firm (if any)			
d. Mailing/Email address			
e. Phone		X	
b. The contacts will be compiled from the list below, as supplemented by the Project Team and the attendees at public meetings: i) Public Agencies ii) Elected/Appointed Officials iii) Transportation Management Organizations of Smart Commute Metro North and Commuting Solutions. iv) Neighborhood Groups v) Property Owners/Tenants vi) Business Interests vii) Special Interests viii) Railroads ix) Media Contacts x) Attendees from public meetings	C	X	
6. Public Notices/Advertisements			
Publicize the proposed project in accordance with the CDOT policies and			
procedures. Copies of the publication shall also be mailed to the individuals on the "contact list".	C	v	
7. Communication Aids	С	X	<u> </u>
	<u> </u>		<u> </u>
a. Graphics Support – provide graphics for presentations and project documents. This may include slides, overhead projector slides, maps and plan views of conceptual design, computerized presentations, three dimensional renderings of no build and build alternative(s) for meeting display and for website use, and other displays for visual presentations at meetings.		X	
 Newsletter – a newsletter which will contain project progress information and announcements will be published at the specified 		X	

	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A p pl ic a bl e
interval and will be distributed to those on the "contact list" specified			
by the CDOT/PM.			
 Local Office – Obtain and maintain an office within the project area to conduct small group meetings and provide displays/information to the public. 			N/A
d. Internet web pages – All external CDOT-related Web sites shall be hosted on CDOT's server and developed in-house with assistance from the Web Team and CDOT Communications. The use of all Web 2.0 and similar social marketing applications on behalf of CDOT (including all regions, divisions and offices) is strictly prohibited unless authorized by the Communications Director. No CDOT employee, contractor or consultant working for CDOT will post			
material on behalf of the agency on such applications without	<u></u>	W	
expressed written consent of the Communications Director. B. PROJECT MANAGEMENT	С	X	
At the kick-off meeting, or shortly thereafter, create and provide an approach for managing the project (i.e. involved staff, key team positions), including task orders, a schedule, document and agency reviews and other project needs. Should the overall project budget be \$500 million or more, an official Project Management Plan (PMP) shall be prepared in accordance with the most recent federal authorization guidance. The Consultant shall coordinate all the work tasks being accomplished by all parties to ensure project work completion stages are on schedule.		X	
C. DEVELOP A PROJECT SCHEDULE AND ASSIGN TASKS			
The Consultant is responsible for coordinating the required work schedule for tasks accomplished by CDOT and other agencies. Prepare the initial project schedule for review by the CDOT/PM and consultant team, and refine to provide detail as requested. Modifications will be made as necessary in collaboration with CDOT and			
appropriate justification.		X	
D. QUALITY ASSURANCE/QUALITY CONTROL (QA/QC) Prepare and submit a QA/QC plan as part of the planning documents noted above, and commit to adhering to the QA/QC process throughout the project. The Consultant will perform a plan review for all milestones (Scoping, FIR, FOR and AD).		X	
E. VALUE ENGINEERING (VE) STUDY A team of transportation design and construction experts will perform a Value Engineering (VE) study. The VE study will be conducted early enough in the project development process to allow evaluation and incorporation of VE recommendations in the NEPA document or design process, as appropriate. The VE study shall be performed in accordance with Federal Highway Administration's (FHWA) current guidelines and recognized techniques and will identify possible alternatives that may save the project cost, time, or other resources. An individual with prior experience and certification in facilitating VE studies (the VE facilitator) shall conduct each VE session. VE facilitators shall be qualified VE practitioners, experienced in performing and leading VE studies (have participated in several VE studies as a team member and several as a team leader), and have sufficient VE training,		X	

	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A p pl ic a bl
education, and experience to be recognized by the Society of American Value Engineers (SAVE) International as meeting the requirements for certification.			
The VE team will consist of individuals with no prior exposure to the project. Individuals that have some familiarity and history with the project shall provide briefings to the team. Consultants or firms shall not conduct studies of their own designs unless they maintain distinct organizational separation of their VE and design sections. The VE team will be assembled to review the Conceptual Background information and plans shall be provided to the team at least three weeks in advance of VE sessions. The VE facilitator will coordinate the study with CDOT, appropriate entities, and FHWA.			
The VE review team will formally evaluate each VE recommendation, and sufficient justification will be made for the acceptance or rejection of each. The VE facilitator will produce a document that summarizes the results, as well as the project elements investigated.			
The Consultant/PM shall prepare a written response detailing which recommendations were not included, the reasons for exclusion, and how all approved VE results will be incorporated into subsequent engineering efforts. These responses shall be forwarded to the CDOT/PM for distribution to the CDOT Region Transportation Director, FHWA, and other appropriate entities. All approved VE proposals shall be incorporated into the final design plans			
F. OBTAIN NECESSARY RIGHT-OF-ENTRY AND PERMITS	<u>:</u>		
Some activities may require work on land not controlled by CDOT. In such cases the Consultant shall obtain the necessary written permission to enter the premises. Written permission shall be coordinated with other CDOT staff and consultants that may need right-of-entry such as geotechnical and environmental personnel. Included in this written permission will be the names and telephone numbers of persons to contact should notification prior to entry be necessary.		X	
Signature Copies	<u>:</u>	Λ	
Permissions apply to CDOT personnel as well as Consultant personnel. CDOT Form 730 may be used for this purpose. Signed copies of written permission will be submitted to the CDOT/PM prior to entering private property for survey work.		X	
2. Permits Some activities such as materials testing on existing pavement and structures may			
require a permit. Permits will be obtained and copies submitted to the CDOT/PM.		X	
G. PROJECT CHARTER			
 Conduct an in-person Project Chartering Session. Generate Project Charter, Containing at a minimum: 			
a. Executive Oversight Committee (EOC)			
b. Chairman of the Project Management Team (PMT) c. Project Management Team	С	X	

	th er *	ta nt	ic a bl e
 d. Technical Task Force Team with each Technical Leads e. Define necessary meetings including frequency and participants f. Define communication flow and decision making process. g. Define Escalation Ladder and Lead. h. All other Roles and Responsibilities. i. Scheduling Approach and Schedule Update frequency. j. Cost Estimation Approach and Cost Estimate Update frequency. k. General Communications, Public Outreach, Stakeholder Engagement framework leading into a separate Communications Plan. 			
H. OTHER PROCESS SUPPORT Assist CDOT with grant writing and submittal. Provide support and advise the CDOT team with the Project Delivery Selection Matrix (PDSM) and Benefit Cost Analysis (BCA).	С	X	

SECTION 6 ENVIRONMENTAL WORK TASK DESCRIPTIONS

Note: This Section is written specifically for projects requiring an Environmental Impact Statement (EIS), an Environmental Assessment (EA), or a Categorical Exclusion (CatEx). It includes elements that are not required for all projects requiring NEPA protocol. Contact Region environmental personnel to determine which items in this section are necessary to address the requirements of the EIS, EA, or CatEx, or post-NEPA activities (ensuring that all of the commitments made by the NEPA document are implemented in the design package). Some tasks and resources are more appropriate depending on the Class of Action. Recommendations for each are made in parentheticals.

Use the CDOT NEPA Manual when completing this section to assure that the level of detail and documentation included meets CDOT expectations and requirements and any other applicable state and federal laws and regulations. Nothing in this Section precludes federal, state, or local agencies or officials from fulfilling their responsibilities under federal, state, or local laws and regulations, NEPA, as codified in 42 United States Code (USC), section 4321, et. Seq., or any of NEPA's implementing regulations.

This list establishes individual task responsibility. Those tasks identified as CDOT/Other should utilize an abbreviation system to indicate whether the task will be completed by CDOT or another agency (i.e. "C" for CDOT and abbreviations as provided below). The consultant shall maintain the ability to perform all work tasks that are indicated below by an 'X' in the consultant column, in accordance with the forms and conditions contained herein, and the applicable CDOT standards. Where appropriate, mark "N/A" for not applicable items.

*Other Agency Abbreviations:

	C D O T (C)/ O th er *	C o n s u lt a n t	N o t A p p li c a b le
A. PROJECT INITIATION	<u> </u>		
1. Environmental Scoping Task (EA)			
An early environmental coordination/scoping task will occur as directed by the CDOT			
Project Manager. An environmental scoping meeting should be held with the			
Environmental Project Manager, resources specialists such as the Regional Water			
Quality Specialist, or appropriate members of the Environmental Programs Branch (EPB), C/PM, and staff from Right-of-Way, Maintenance, Hydraulics,			
DTD, Division of Transit and Rail, and Region Traffic, Property Management,			
FHWA, and Utilities, as appropriate. This task will include a meeting with CDOT			
and the local agency representatives to discuss the initial work efforts of the			
project. Traffic modeling usually dictates the alternative evaluation process.			
Determine if macroscale, mesoscale, and/or microscale modeling is required for			
the project.	С	X	
2. Extent of Study Required for Resources (EA)		X	

Determine the extent of study required for each resource area. The extent of study			
can be defined in four categories: 1) complete analysis required; 2) short			
analysis to define resources/impacts; 3) no analysis required; or 4) analysis			
already completed (for example, by a previous study).			
3. Project Study Area Limits/Logical Termini (EA)			
Preliminary project study area limits are established in Section 1 of the Generic Scope			
of Work document. Perform necessary research and data collection to propose a			
study area boundary for environmental resources and logical termini for use in			
scoping. In coordination with the CDOT/PM, prepare a recommendation to the			
FHWA for approval of the logical termini, if applicable.	C	X	
4. Project File (EA)			
Maintain a Project File, set up similarly to the established process for a NEPA			
Administrative Record. Make available all parts of this project file to the			
CDOT/PM (or his or her designee), or to the Colorado Attorney General's office			
(as requested) at any time during the project's duration. All materials associated			
with the project file shall be delivered in the format specified by the CDOT/PM			
when closing the project. Final project invoice payments to the Consultant are			
conditional upon the professional and complete delivery of these materials to			
CDOT's office. Given the extent of documentation collected for the NEPA			
process, the consultant shall update the record regularly and provide information			
to CDOT electronically. See CDOT NEPA Manual for additional guidance.	С	X	
5. Review Applicable Existing Documents (EA)			
Review project-specific documents or data related to the assessment of			
environmental, social, and economic resources and impacts in the project area			
that are determined relevant. These resources may be CDOT documents or may			
have been created by local planning agencies or municipalities.		X	
B. ENVIRONMENTAL ANALYSIS AND DOCUMENTATION			
1. Purpose and Need (EA)			
Develop a solid Purpose and Need statement, reviewed, and approved by appropriate			
parties. The objectives of the project should be clearly identified and agreed upon			
early in the project process to prevent backtracking and limit schedule changes.			
Develop and refine, as necessary, to address information collected on the project			
during data collection, transportation analysis, and public and agency scoping and			
involvement. Review previously prepared studies to help direct Purpose and Need			
information as appropriate (e.g., local planning studies, engineering feasibility			
studies, etc.). Submit the Purpose and Need for review and approval by CDOT			
and FHWA.	С	X	
2. Alternatives Development and Evaluation (EA)			
Develop a range of reasonable multi-modal alternatives (including but not limited to			
bike, pedestrian, and transit modes) that will satisfy the Purpose and Need			
requirements of the project, including, but not limited to, those identified in			
earlier and ongoing studies of the area. The Consultant team, in coordination with			
CDOT and FHWA, will determine the design year to use for the project. Changes			
in the design year during the project may be subject to a Scope of Work		37	
modification.	С	X	
3. Alternatives Screening Process (EA)			
Apply an alternatives screening process to identify the reasonable alternatives			
(practical or feasible from a technical and economic standpoint), which will be			
subject to a more detailed evaluation. Develop NEPA-appropriate evaluation			
criteria, and measures of effectiveness, and submit them for review and approval			
by CDOT and FHWA before beginning the screening process. The rationale for eliminating alternatives will be thoroughly discussed within the documentation.		X	
	<u>:</u>		
4. Preliminary Design of Alternatives (EA)	<u> </u>	X	

For each alternative that passes the screening process, incorporate preliminary design to a level that clearly allows the identification of impacts within each	
environmental resource area. These alternatives may be carried through the entire	
analysis process until a decision document is written. If CDOT or another agency	
or Consultants performs selected alternative studies, the Consultant shall	
incorporate the results of these studies into the appropriate document.	
5. Evaluate Alternatives Impacts (EA)	
Apply projected design-year traffic volumes and projected opening day traffic	
volumes for new facilities as developed for this Scope of Work, or as modified	
through later studies and calculations by CDOT. Evaluate the impacts of these	
alternatives according to established guidelines and examine the degree to which	
these alternatives satisfy the Purpose and Need requirements of the project. Set	
out these evaluations both schematically and in narrative form for review within	
a reasonable time after the Notice to Proceed.	X
C. COST ESTIMATES AND FINANCIAL ANALYSIS	
1. Preliminary Construction Cost Estimates (EA)	
Prepare preliminary construction cost estimates based on 10%, 30%, 90% (FOR),	
SHELF, AND ADVERTISEMENT design the alternatives identified during	
the NEPA process. Project right of way acquisition and project environmental	
mitigation costs shall be included within the cost estimate. Include enough detail	
to ensure a reasonable degree of accuracy for the level of design performed.	
Submit the format of estimates, including the year from which the unit costs	
were assumed, to CDOT's Project Engineer for review and approval.	37
Incorporate the analysis into the NEPA document.	X
2. Develop Cost Estimates and Financial Analyses (EA)	
As part of evaluating reasonable alternatives in the NEPA document, including the	
No-Action Alternative, develop cost estimates and financial analyses at varying	
levels of detail throughout the process in coordination with FHWA. Basic	
engineering, preliminary engineering, construction engineering, construction, and	
operating/maintenance for the design life shall also be analyzed. A funding	
package identifying the funding sources necessary to construct and maintain the projects will be developed. FHWA requires preparation of a financial plan for	
major projects over \$100 Million. See FHWA Major Project Guidance.	
Consultant shall be responsible for its preparation. Review the cost estimates and	
financial analysis, provide supplemental analysis as needed to support the	
Preferred Alternative, and incorporate findings into the draft NEPA document.	X
D. DATA COLLECTION, FIELD INVESTIGATION, MITIGATION	A
- 17 1763 175 3 3 7 1 7 17 7 7 1 1 1 7 1 3 1 1 1 1 1	: :

The following analyses are required for each of the alternatives that pass the screening process. Each resource will be summarized, focusing on the project issues of concern. The scope shall define the level of documentation, project tasks, and project deliverables for each of the resource areas. Identify the required area and resources to evaluate and determine the early coordination/scoping process as discussed above. This may evolve over the life of the project as new information is discovered through analysis. The level of detail and analysis will be determined based on study and its appropriate level of environmental documentation (e.g., Feasibility Study, CatEx, EA, or EIS). Deliverables can be static reports, digital reports, and/or GIS data layers. The scope should be specific as to what type of deliverable is expected. It is anticipated that the level of detail for this NEPA document will be as appropriate for an EA (Environmental Assessment). Technical documents were previously prepared for the I-25 (US 36 to 104th Avenue) draft Environmental Assessment in 2020. For each resource, review the appropriate technical documents and update (as necessary) to 2023 conditions. Follow CDOT NEPA Manual for guidance on methodology and level of detail.		X	
1. Air Quality and Greenhouse Gas Emissions (EA)	<u>:</u>	Λ	
a. Perform the necessary air quality assessment and MOVES emissions inventory as required under state and federal statutes and regulations, and provide the results for integration into the NEPA document and Air Quality Technical Report (with modeling data assumptions), in conformance with the requirements of the CDOT Air Quality Project Level Analysis Guidance (AQ-PLAG). These will include, but are not limited to, analysis or discussion of the NAAQS (criteria pollutants), regional emissions analysis, Mobile source air toxics (MSAT), greenhouse gasses (GHG), climate change, construction issues such as fugitive dust emissions, and mitigation measures. Use the new CEQ Guidance from Jan. 9, 2023 (FR Vol. 88, No. 5) "NEPA Guidance on			
Consideration of Greenhouse Gas Emissions and Climate Change," Colorado Revised Statute (CRS) § 43-1-128 (also referred to as Senate Bill [SB]-260), and the CDOT SB 21-260 Interim Guidance to evaluate No Action and Build Alternative(s) contribution to greenhouse gas emissions.	C	X	
b. CDOT staff will lead coordination with the Colorado Department of Public Health and Environment Air Pollution Control Division (CDPHE-APCD), FHWA and U.S. Environmental Protection Agency (EPA) (as necessary). The analytical methodologies will be determined through the interagency coordination. Each Build Alternative and the No-Action Alternative will be analyzed for impacts through the appropriate design year. Mitigation and air quality monitoring commitments will be developed, as necessary. Utilize the most current standard, accepted FHWA language for MSATs. Consultant to consider Electric Vehicle (EV) charging as a mitigation strategy. Review existing technical documents and update as necessary.	С	X	
2. Water Quality (EA)			
a. Affected Environment: Investigate and document the status of the water resources (quality, etc.) for the purposes of describing the existing condition or "affected environment" before construction: groundwater, aquifers, lakes, rivers, streams, and springs, locations of drinking water treatment plants, Permanent Water Quality Control Measures and locations of sewage treatment facilities.		X	

	-	·	·····
b. Environmental Consequences: Investigate and document the impact			
the project, to water resources (quality, etc) and quality impacts of t			
project during and following construction. Determine mitigation by			
considering the project location and design concepts in relation to			
existing water resources including groundwater or alluvial waters or	r		
aquifers (particularly sole source), drainage ditches and other State			
Waters as defined by CDPHE Water Quality Control Division, aqua			
well as riparian habitat, and Sensitive Waters (Class 1 Aquatic Life,			
Recreation 1, and Water Supply, 303[d] listed, etc).		X	
c. MS4 Permit requirements WILL apply to this project. Determine th			
requirements of the CDOT and Local Agencies Municipal Separate			
Storm Sewer System (MS4), Colorado Discharge Permit System			
(CDPS), and design and permitting. Determine the requirements of	the		
CDOT and Local Agency MS4 PWQ program.		X	
d. Recommend appropriate Water Quality mitigation measures as			
necessary. A mitigation plan that includes conclusions of effects,			
permanent water quality (PWQ) control measure (CM),			
temporary/construction CMs, erosion control measures, and definiti	on		
of maintenance responsibilities.		X	
e. Deliverable: Prepare Water Quality Technical Report. Consultant to			
review existing technical documents and update as necessary.		X	
f. Coordinate with local agencies on permanent water quality facilities	s C	X	
3. Wetlands and Waters of the U.S. (WUS) (EA)			
a. Wetlands Determination/Delineation:	C	X	
i. Review existing Wetland Finding report. Confirm presence or a	ı		
absence in the field. Update any maps as necessary using Globa			
Positioning System (GPS) or survey equipment should be used			
this activity.		X	
b. If needed, consultant to update the delineations of the boundari	es of		
all anticipated jurisdictional and non-jurisdictional wetlands an			
waters of the US within the project area using United States Ar			
Corps of Engineers (USACE) guidance listed in Appendix A. I			
to be provided to CDOT in the correct format – i.e. shapefiles v			
information separated in a report or memo.		X	
c. If needed, prepare updated maps that delineate the wetland			
boundaries within the corridor. The ordinary high water mark s	hould		
also be delineated, as appropriate. GPS will be used for this			
mapping.		X	
d. Coordinate the findings with the CDOT Region and if requested	d by		
the region, with the USACE. If requested by the CDOT Region			
obtain jurisdictional determination of the wetlands from the			
USACE.	C	X	
b. Wetland Finding Report			
Review the existing Wetland Finding Report and update as necessary			
according to CDOT's most recent guidance/checklist. The Functional			
Assessment of Colorado Wetlands (FACWet) should be used, as appropri			
according to current CDOT procedures. Conduct a wetland assessment by			
on the NEPA document addressing the amount of permanent and tempor			
wetlands impacts and mitigation. Wetland mitigation should be identified	d as		
early as possible in the NEPA process. All wetlands will be considered			
jurisdictional for mitigation purposes. CDOT will determine the type of			
mitigation $-$ i.e. bank or onsite. Mitigation sites must be evaluated for			
availability and suitability for wetland habitat.	C	X	
4. Vegetation and Noxious Weeds (EA)			

	D-'		<u> </u>	
	a. Review existing technical reports and update as necessary. Confirm			
	assessment in the field for the Affected Environment. Investigate (GIS			
	and field) and document the status of vegetation habitat and noxious			
	weeds for the purposes of describing the existing condition or "affected		v	
	environment" before construction		X	
	b. Review the Environmental Consequences: Investigate and document			
	the impacts of the project, to vegetation habitat and noxious weeds		37	
	during and following construction.		X	
<u>'</u>	c. Recommend appropriate vegetation habitat and noxious weed		37	
	mitigation measures as necessary.		X	
	d. Review and update an Integrated Noxious Weed Management Plan to		3.7	
	be prepared with the NEPA document.		X	
	e. Deliverable: Review and update a Vegetation Habitat and Noxious			
	Weed Technical Report, and review and update the respective Noxious	~		
	Weed mapping in GIS as necessary.	С	X	
5.	Fish and Wildlife (EA)			
	a. Conduct necessary field surveys (including migratory birds and raptors)			
	and identify fish and wildlife and their habitat within the project area. As			
	appropriate, GPS will be used to identify habitat.			
			X	
	b. CDOT staff will lead coordination with the Colorado Parks and Wildlife			
	(CPW) Colorado Division of Wildlife (CDOW) and US Fish and			
	Wildlife Service (USFWS)	С	X	
	c. Perform an impact analysis.		X	
	d. Develop appropriate mitigation measures		X	
	e. Review existing Wildlife Report and update as necessary	С	X	
6.	Threatened and Endangered (T&E) Species (EA)			
:	a. CDOT staff will lead coordination with USFWS to determine if T&E			
	species or their habitat exists in the project area.	С	X	
	b. Review the existing Technical Report for Threatened and Endangered			
	Species and update as necessary. Conduct updates as needed for desktop			
	and field surveys and identify T&E species and/or Designated Critical			
	Habitat.		X	
	c. Review existing planning documents to determine any existing Habitat			
	Conservation Plans (HCP) under Section 10, if necessary, for T&E			
	species.		X	
	d. Review existing planning documents to determine need for a Biological		- 11	
	Assessment/Biological Opinion under Section 7 for the USFWS if			
	federally listed T&E species and/or Designated Critical Habitat will be			
	impacted and there is a federal nexus.		X	
	e. Develop a HCP under Section 10 and/or Biological		-12	
	Assessments/Biological Opinions under Section 7, if necessary, with the			
	USFWS if T&E species and/or Designated Critical Habitat will be			
	impacted and if there is a federal nexus.		X	
	f. Identify any impacts and develop a mitigation plan to conform to		- Z L	
	namainamanta afeta Endamana Consider Ale		X	
7	Historic Properties (EA)		11	
ļ				
	a. Review existing technical reports and update as necessary. Perform and			
	provide the survey report for review by the CDOT Region Historian or			
	EPB Senior Staff Historian, and incorporate the information into the	~	37	
	NEPA document. The following lists are not meant to be exhaustive.	С	X	
	b. Collection and Evaluation of Baseline Information as defined by Section			
	106 of the National Historic Preservation Act of 1966, as amended The		***	
	scope of work for historic properties compliance varies depending on the		X	

project. The list below represents a typical scope of work, but			
consultants should coordinate with CDOT staff to determine the level of			
effort for each project. CDOT staff is very hands-on when it comes to its			
Section 106 compliance responsibilities. Consultants should never			
contact SHPO staff or submit any material without CDOT oversight and			
approval.			
c. Historic Clearance		X	
i. Identify the area of potential effect (APE), in coordination with			
CDOT and the State Historic Preservation Officer (SHPO).	С	X	
ii. Conduct literature and records search for previously recorded			
historic resources in the APE in the OAHP. Compass database.		X	
iii. Conduct an architectural field survey of the APE and determine			
National Register of Historic Places (NRHP) eligibility for			
resources at least 50 years old. Age of resources evaluated may			
vary depending on when the project will be constructed.			
Potential resources include man-made structures, ditches,			
railroads, etc. Level of effort (e.g., reconnaissance, intensive)			
for the survey may vary depending on the project scope and			
schedule and should be coordinated with CDOT staff.		X	
iv. In coordination with CDOT staff, identify and coordinate with			
consulting parties (e.g., public, historic preservation groups,			
local historical societies, museums) regarding historic			
properties in the project area and meetings to discuss project			
updates and Section 106 findings.	С	X	
v. Prepare a comprehensive Survey Report according to guidelines			
established by the OAHP to submit for review by the CDOT			
Region and/or EPB Senior Staff Historian. The report will			
include historical context information and other data to support			
eligibility determinations. Make revisions as requested by			
CDOT.		X	
vi. Determine potential effects, both direct and indirect, to historic			
resources and recommend strategies to avoid, minimize, or			
mitigate impacts. Depending on project scope, consultants may			
prepare a separate effects report for review by CDOT. Region			
or EPB historians.		X	
vii. Prepare draft correspondence as necessary for the CDOT			
Region and/or EPB Senior Staff Historian to submit to the			
SHPO. In some circumstances, consultants are asked to deliver			
submittals to SHPO and consulting parties.	С	X	
viii. When there are adverse effects, collaborate with the CDOT			
Region Historian or EPB Senior Historian to identify possible			
mitigation and assist in development of a Memorandum of			
Agreement, for agency review and execution. Note that			
mitigation and development of MOA is typically completed by			
CDOT staff.	С	X	
ix. Prepare draft Section 4(f) documents as required. In most cases,			
CDOT staff will prepare documentation of Section 4(f)			
exceptions and de minimis findings Consultant assistance may			
be needed for programmatic and full evaluations.	С	X	
8. Archaeology (EA)			
a. Review the existing technical reports and update as necessary. A review			
of historic Sanborn Fire Insurance maps and other appropriate archival			
sources will be completed to determine if the area may contain			
significant archaeological sites or features.		X	
	······	<u></u>	

		Conduct an intensive field survey of the project corridor(s) and undertake site-specific test excavations, as necessary and appropriate, to determine NRHP eligibility. The Consultant shall not undertake test			N /
		excavations before consulting with CDOT.			A
	c.	Complete laboratory analyses of all collected artifacts and ancillary specimens.			N /
		specimens.			A
		Review existing survey report according to guidelines established by the OAHP.	С	X	21
		Develop a data recovery plan to mitigate potential adverse effects to			<u>.</u>
		significant archaeological localities, as appropriate and necessary.		X	
		Coordinate the mitigation plan with the EPB Senior Staff Archaeologist,		37	
		appropriate Region staff, SHPO, and other required agencies.	С	X	<u> </u>
		Conduct data recovery excavations at any significant archaeological site		***	
		that cannot be avoided during construction.		X	
		Analyze artifacts.		X	
		Prepare and submit a data recovery excavation report which describes, in			
		a thorough and comprehensive fashion, the project results and the nature			
		of the site in the context of the regional archaeological database. The			
		report must also include site management recommendations in the			
		context of the NRHP.		X	
	j.	CDOT staff will lead coordination and Tribal consultation. Support EPB			
		Senior Staff Archaeologist as needed.	С	X	
	k.	Prepare Section 4(f) documents as required.		X	
9.	Pale	eontological Resources (EA)			
		Perform a literature and museum fossil database search and field			N
		assessment.			/ A
	b.	Determine the presence or absence of paleontological resources.			N / A
		Conduct analysis to determine the scientific significance (research and/or educational value) of the resource.			N / A
:	d.	Review the existing paleontological technical report and update as			
		necessary, including mitigation proposals, if necessary. The assessment			
		report will be reviewed by the EPB Staff Paleontologist for adequacy.	С	X	
		Coordinate the mitigation plan with the EPB Staff Paleontologist, and			
		appropriate Region staff.	С	X	
10		tion 6(f) Evaluation (EA)			
		Review existing technical reports and update as necessary. Inventory			
		and map project area for Section 6(f) resources using CDOT's Online			
		Transportation Information System (OTIS).		X	
	b.	Determine if any potential impacts or ROW acquisitions include			
		Section 6(f) resources.		X	
	с.	Evaluate project impacts on Section 6(f) properties using preliminary	<u> </u>		<u>.</u>
	v.				
		design information, and the necessary commitments for mitigation measures. Determine whether impacts qualify as a temporary non-conforming use or a park improvement. Document the level of impact, all practical alternatives to the conversion, and avoidance and			
		measures. Determine whether impacts qualify as a temporary non-conforming use or a park improvement. Document the level of			

d. If a full conversion is required, CDOT staff will lead coordination with Colorado Parks and Wildlife (CPW) to find a replacement property that is of equal fair market value and equivalent use of the property being converted. Purchase and document conversion of the property using National Park Service guidance.	C	X
11. Section 4(f) Evaluation: Please note that there are separate requirements for historic and non-historic Section 4(f) evaluations (EA)		
a. Review existing technical reports and update as necessary. Inventory and map project area for possible Section 4(f) resources.		X
 Determine if any potential impacts or ROW acquisitions include Section 4(f) resources (e.g., publicly owned parks, recreational facilities, nationally significant historic sites, wildlife refuges). 		X
c. Determine and evaluate project impacts on Section 4(f) resources using preliminary design information, and the necessary commitments for mitigation measures. Determine whether impacts require an exception, <i>de minimis</i> , programmatic, or individual 4(f) evaluation. Prepare an analysis that includes avoidance alternatives, discussion of prudent and feasible, least harm (if necessary), minimization, and mitigation related to Section 4(f) resources. This may include the development of a new alternative(s) as an avoidance alternative(s). Prepare the appropriate documentation in consultation with CDOT Region or EPB Staff.	C	X
d. Develop Official with Jurisdiction (OWJ) concurrence request letters (if necessary. For non-historic resources, OWJ will vary. For historic properties, the SHPO is the OWJ and the Section 106 consultation correspondence helps to inform the Section 4(f) process.	C	X
12. Noise (EA)		
 a. Review existing technical reports and update as necessary. Prepare a traffic noise analysis in accordance with the most recent CDOT Noise Analysis and Abatement Guidelines, and submit a complete Traffic Noise Technical Report to CDOT for review and acceptance. The analysis will consist of the following, each of which must be documented in the Traffic Noise Technical Report: 		X
 Definition of relevant noise abatement criteria and identification of noise-sensitive land uses. 		X
ii. Validation of the traffic noise model and determination of existing noise levels (by measurement and modeling) under current conditions.		X
iii. Prediction of future traffic noise levels for all alternatives, including the No-Action Alternative, using FHWA's current Traffic Noise Model.		X
iv. Determination of traffic noise impacts.		X
v. Identification and evaluation of the feasibility and reasonableness of noise abatement measures. Coordinate with the Project Engineer with regard to the locations and heights/lengths of proposed abatement measures.		X
vi. Development of recommendations regarding noise abatement measures (i.e., optimized barrier design).		X
vii. Assessment of construction related noise issues. b. The above items will be addressed and documented in a Traffic Noise Technical Report, which will be prepared and submitted to CDOT for review and acceptance. Prior to beginning this work, the Consultant	C	X

shall meet with the CDOT Noise Specialist to review the appropriate	<u> </u>	Ī	·····
shall meet with the CDOT Noise Specialist to review the appropriate methodology, measurement/validation points, and noise study zone.			
Noise modeling should be completed for the model year 2050. The			
draft and final technical report will be completed and made available to			
the CDOT Noise Specialist and appropriate Region staff for review; the			
findings will be incorporated into the NEPA document.	<u>. </u>		
13. Hazardous Materials (EA)			
Perform and document the following Modified Environmental Site Assessment			
(MESA) activities:			
a. Review the existing MESA and update as necessary. In accordance			
with CDOT Hazardous Materials Guidance, conduct regulatory			
research that includes the collection, mapping and evaluation of data.			
Prior to beginning this work, the Consultant shall meet with the CDOT	~		
Hazmat Specialist to review the appropriate methodology.	С	X	
b. Analyze results of regulatory research and records review and identify			
potential impacts construction activities may have on existing			
hazardous waste sites. Assess potential liability issues and hazards to			
the public, construction workers, and the environment then develop			
potential mitigation options. Prepare the MESA Document to include			
the following:		X	
i. Prepare the draft and subsequent final MESAs to address			
comments provided by CDOT. The findings will be			
incorporated into the NEPA document.	С	X	
ii. MESAs will emulate industry standards for Phase I reports			
(with limitations), and make a determination of the necessity			
of a Phase II report.	<u> </u>	X	
iii. Identify how the presence of hazardous waste locations may			
impact each alternative, including the no-action alternative.			
GIS mapping will be desired.		X	
c. Conduct In-Situ Tests such as lead-based paint and asbestos testing as			
necessary, and provide a survey report, as determined on a			
project-specific basis.	<u> </u>	X	
d. Phase II site assessment if necessary for the alternatives screening			
process.		X	
14. Community Understanding Report for Land Use, Social, Economic,			
and Environmental Justice Resources (EA)			
Consultant shall review prior completed technical reports for land use, social			
resources, economic resources and environmental justice communities.			
Consultant shall create a new Community Understanding technical report which			
will (1) evaluate the existing conditions for land use, social resources, economic			
resources, and environmental justice communities for the project corridor, (2)			
analyze, quantify and describe the potential effects of the build and no build			
alternatives on these conditions, and (3) propose avoidance, minimization and			
mitigation strategies for any adverse effects to these resources.			
Methodology to complete the Community Understanding Report shall include,			
but not be limited to:			
Review and update mapping as necessary: baseline information for			
existing land use. Prepare information on land use and zoning,			
including maps of existing, planned and future uses. Prepare land use			
mapping. Mapping may include parcel use categories such as land in			
public ownership, commercial, retail, wholesale, industrial, residential,			
vacant, mixed etc. identifying jurisdictional boundaries and land usage			
along each alternative. (Information may be obtained from the	<u> </u>	X	

	addresses, estimated areas of impacts per parcel, type of impact i.e. – full or partial acquisition, temporary or permanent easement, and			
	a. Prepare a table identifying and listing all potentially affected properties including, at a minimum, ownership names, property and mailing			
	in accordance with Title 23 CFR 710:	С	X	
	manager (or designee), or Headquarters ROW specialist assigned to the project,	_		
	member of the Consultant team, in coordination with the CDOT Region ROW			
	The following activities will be performed and documented by a qualified			
	15. Residential/Business/Right-of-Way (ROW) Relocations (EA)			
	communities in accordance with the CDOT NEPA Manual.			
	efforts and input (or feedback) for low-income and/or minority			
	from low-income and/or minority populations. Document all outreach			
	and Title VI outreach activities necessary to obtain sufficient input			
	CDOT's EEO Office to determine the level of Environmental Justice			
	specialist, CDOT's Environmental Justice and Equity Branch, and			
	measures development. Collaborate with EPB's Environmental Justice			
	impact analysis, preferred alternative identification, and mitigation			
	development of purpose and need, alternatives analysis and screening,			
	class of action, meaningful opportunity to comment on or related to the			
	opportunity to provide input in the NEPA process, as dictated by the			
	low-income or minority populations have been afforded the			
	Understanding report, document the degree to which affected			
	community to provide input to the project exist. In the Community			
	plan, ensure that meaningful opportunities for all members of the			
	As part of implementing the project's public stakeholder involvement			
	water pollution, aesthetics, community cohesion, relocation impacts).			
	will cross-reference other resources as appropriate (e.g., noise, air and			
	the project on these populations will also be identified. The analysis			
	CDOT NEPA Manual and Executive Order 12898. Beneficial effects of			
	Impacts to these communities will be evaluated in accordance with the			
	mitigate the impacts according to environmental justice guidelines.			
	measures for the alternatives that would avoid, reduce/minimize or			
	and adverse effects of build and no build alternatives. Develop			
	potentially effected by the project alternatives. Analyze both beneficial			
	populations and other disproportionately impacted communities (DIC)			
	applicable data to identify existing low-income and minority			
	 Review, update and map as necessary, the U.S. Census data and other 			
	as part of a continuative circum analysis, as appropriate.			
	well as part of a cumulative effects analysis, as appropriate.			
	employment. This will be done at the regional and corridor level, as			
	recent Census data shall be utilized for understanding communities and			
	employment, local tax base, regional earnings, etc. When relevant,			
	project alternatives on commercial and industrial enterprises,			
	accessibility of facilities and services. Investigate the effects of the			
	investigate and document the effects of the project alternatives on community cohesion, safety and security, neighborhoods, and			
	Review and update mapping as necessary: baseline information to investigate and document the effects of the project alternatives on			
	county, and/or from field verification.)			
	maps, Sanborn maps, archival aerial photos, the local city, town or			
	Department of Local Affairs, County Assessor Maps, DRCOG planing			

the state of the country to the state of the			
the discretion of the CDOT Region and/or Headquarters ROW staff.			
b. Perform a ROW field inspection of each short-listed alternative.			
Ascertain number of parcels, types of improvements, and possible			
issues (e.g., historic sites). Estimate family sizes for residential		W	
relocations.		X	
c. Compile a ROW acquisition and relocation cost estimate for the		37	
alternatives.		X	
d. Prepare a property ownership map based on tax records, which		37	
identifies ownerships for the alternatives.	C	X	
e. Develop and document mitigation measures	С	X	
16. Utilities and Railroads (EA)			
Collect utility location key maps for all existing and planned utilities in the area			
in coordination with the CDOT Region utilities specialist. Conduct all field			
utility locates. The potential impacts on or from utilities in the project area will			
be analyzed as well as any appropriate mitigation measures. Follow CDOT		37	
NEPA Manual, Chapter 9 for guidance on evaluation and documentation.	С	X	<u> </u>
17. Farmlands (EA)			
(For unique circumstances) In coordination with the Natural Resource			
Conservation Service (NRCS), investigate and quantify the effect of the project			
alternatives on farmlands—determining whether farmlands in question are			
classified as "prime" or "unique," as well as the extent to which impacts may			
affect local communities. The US Department of Agriculture Farmland			
Conversion Form (Form AD 1006) will be completed as necessary. Identify			
impacts and recommend appropriate mitigation measures as necessary. Follow			
CDOT NEPA Manual for additional guidance on evaluation and documentation.			N
Follow the current version of CDOT's Visual Impact Assessment (VIA) Guidelines as found on the CDOT Landscape Architecture Website. Complete			
items a, b, and c prior to obtaining a consultant or in some cases they are		X	
completed by the consultant.	<u>. i</u>	Λ	<u></u>
a. Review existing technical reports and update as necessary. Conduct			
Pre-Scoping (Step E-1): The CDOT NEPA practitioner coordinates			
with the project team to understand the project scope, location, context,			
and visual attributes. The CDOT VIA practitioner and/or consultant completes Step E-1 in the VIA Guidelines, by following the sequence			
of steps in the Decision Tree (Figure 3), to determine if there is a			
potential for visual impacts and whether to proceed with the VIA			
Scoping Process.			
scoping flocess.			
If a VIA is not required, based on Pre-Scoping, email Pre-Scoping			
documentation to the Environmental Project Manager and no further			
action is necessary.			
action is necessary.			
If the Pre-Scoping process determines that a VIA may be necessary,			
continue to next steps in the scoping process.	С	X	
b. Conduct Scoping: Complete steps E-2 through E-5 in the VIA		Λ	
Guidelines. In coordination with CDOT staff, the CDOT VIA			
practitioner or consultant completes the Scoping Questionnaire to			
determine if a VIA is required.			
determine if a vira is required.	C	v	

included in the NEPA document (without personal property details) at

	practitioner and project engineer for determining public involvement opportunities. (Reference Chapter 7, Stakeholder Involvement Plan, in		
	opportunities. (Reference Chapter 7, Stakeholder Involvement Plan, in the CDOT NEPA Manual).		X
d.	Conduct Scoping (Steps E-6 and E-7): Define the Area of Visual Effect and Delineate Landscape Units.		X
e.	Prepare visualizations: Coordinate with the CDOT NEPA practitioner and project engineer to determine the appropriate level of project visualizations for communication, assessing visual impacts, and facilitating public input. The appropriate level of visualizations may vary by project, to reflect the available level of project design (conceptual, preliminary, or final), and present an accurate scale and representation of details. Refer to the Visualization Matrix (Appendix D of the VIA Guidelines) for guidance in applying 3D visualization and conceptual modeling software, and image enhancement software.		
	Graphics may include cross-sections, hand drawn sketches, simulations (with site current site photos (whenever possible) and/or 3D graphics; or augmented/virtual reality fly through of key viewpoints.		X
f.	Create content for CDOT Active Projects Webpage. May include site maps, photographs, renderings, videos, and a project write up.		X
g.	Complete Visual Resource Inventory and Analysis: follow and apply CDOT VIA Guidelines, templates, and tools.	С	X
h.	Complete NEPA Mitigation commitments (if applicable, developing design guidelines can be made a commitment and completed after CATEX/EA/EIS) Track mitigation measures in CDOT's Mitigation Tracking Spreadsheets, NEPA Manual Tables 9-1 and 9-2.		X
i.	Develop Design Guidelines, to be completed prior to FIR (30% Design) in order to inform and be incorporated into the design – <i>if applicable</i> .	C	X
j.	Project Delivery - (incorporate mitigation measures and NEPA commitments into design – Preliminary and/or Final).	C	X
k.	Construction Phase - and field mitigation/design oversight, for design compliance. (CDOT LA or Region Mitigation Coordinator)		X
1.	Post-construction monitoring - of irrigation and plant establishment success and health if applicable. (CDOT LA)	С	X
Review docume investig alternat not lim potentic sites, et	cologic Resources and Soil (EA) rexisting technical reports and update as necessary. Perform and tent in the NEPA Document, and a Geologic Technical Report, a thorough gation of the project area to determine possible geologic influences on the tive designs under consideration, or vice versa. Constraints, including but itted to major excavations, unsatisfactory sub-grade materials, present and al subsidence, potential for rockfall, the presence of abandoned mine icc., will be evaluated. This task includes consideration and description of cidor water table (i.e., depth/gradient).		X

a. b.	Review existing technical reports and update as necessary. Consistent with CEQ regulations, the cumulative effects of each proposed action on a resource, ecosystem or human community will be evaluated for each alternative. The analysis will both list and consider incremental impacts of each alternative in conjunction with all past, present, and reasonably foreseeable future actions, no matter what entity (federal, non-federal, local government, or private) is taking or has taken the action; but the analysis should only focus on meaningful effects. Develop the scope of the analysis in consultation with FHWA and CDOT, and, in general, will base temporal and spatial boundaries on the natural boundaries of resources of concern and the period of time that the proposed action's impacts will persist. The analysis will be incorporated into the NEPA document, and mitigation measures specific to cumulative impacts, if needed, will be identified Standard FHWA global climate change language (found in NEPA	C	X	
	Manual Appendix F) is to be incorporated within every cumulative impacts section of a NEPA document.	_	_	
21 Two	ansportation Resources (EA) (include bike, ped, and transit	С	X	
•	erations)			
a. b.	Review existing technical reports and update as necessary. Develop traffic volumes using available traffic demand models; determine the design year during the scoping process for the project. The model expected to be used for this project is the official Metropolitan Planning Organization model, if one is available for the project area, or the official CDOT Statewide Travel Demand Model if the project's study area is not contained inside an MPO area 2050 model. The method for traffic modeling will be determined at the beginning of the project upon FHWA approval. Forecasts should be based on existing roadways and roadways that are committed to be constructed (that is, "No Action"—those that will be constructed regardless of whether the project in question moves forward). Future traffic forecasts must be developed for the No-Action Alternative and any build alternatives. The results of the travel demand forecast process will be developed into a technical report. Collect all data needed to calibrate the Travel Demand Model and		X	
	Microsimulation models.		X	
c.	Analyze existing and future traffic operations analysis will be conducted for the No-Action Alternative and build alternative(s). Analysis will be completed in accordance with the latest edition of the Highway Capacity Manual or similar methodology. In addition, the Consultant shall use a micro simulation software package (i.e., CORSIM, TransModeler, VISSIM, Dynasmart-P, or others as approved by CDOT) to evaluate the operations of the entire roadway network and report the appropriate measures of effectiveness for the alternative(s). The selection of the software package for the required analyses will depend on the size and other characteristics of the network, the alternatives to be analyzed, and the measures of interest. At a minimum, analysis will consider existing traffic volumes, accident history, percent of truck traffic, directional splits on all arterials, turning movements at intersections, interchange and ramp characteristics, travel/access patterns, level of service, delays, travel times and speeds, and areas of congestion. During the alternatives development and evaluation process, the appropriate level of operations analysis will also be conducted on the alternatives being considered. The results of	C	X	

the operations analysis are documented into a Transportation Technical Report.			
 d. Conduct safety analysis and document accident rates based on data collected from local emergency services, Colorado State Patrol, and CDOT Traffic Analysis Unit; obtain weighted hazard index from CDOT/PM; evaluate trends; document safety issues and how they can be addressed. 	C	X	
e. Bicycle and Pedestrian Facilities Research and identify existing and future planned bicycle and pedestrian facilities in the project area. The necessary data will be collected from project design documents, community transportation plans, local land developers, open space and park trails, or local governmental agency or community interest groups to determine if any facilities will be impacted, and as a result what mitigation is necessary. If the corridor is a heavily traveled biking facility, the scope of work shall include meetings to coordinate with bike users throughout the NEPA process. Coordinate with the CDOT Region Bike and Ped Liaison, and identify impacts and recommend appropriate mitigation measures as necessary. Follow requirements in CDOT Policy Directive 1602. A summary of the findings will be included in the Transportation Technical Report.	C	X	
22. Energy (EIS) (For unique circumstances) Discuss in general terms the construction and operational energy requirements and conservation potential of various alternatives under consideration. The discussion should be reasonable and supportable. A calculation of energy consumption during construction should be included. If applicable, follow CDOT NEPA Manual for guidance on evaluation and documentation. E. DELIVERABLES			N / A
The following documents will be considered as official deliverables. Deliverables to CDOT will occur at the dates agreed to within the project contract and related agreements.		X	

 Logical Termini Memo Purpose and Need Memo Alternatives Development and Screening Memo Cost Estimate, Financial Analysis, and Funding Options Memo Air Quality Technical Report with emphasis on Greenhouse Gas Emissions Water Quality Technical Report Wetland Finding Report Vegetation Habitat and Noxious Weed Technical Report and project Noxious Weed technical report & GIS mapping Wildlife and T & E, and Sensitive Species Technical Report Cultural Resources Survey Report Archaeological Survey Report Draft Cultural Resources Section 4(f) documents as required Paleontological Technical Report Recreational Resources including Section 4(f) and Section 6(f) Eligible Properties Technical Report Section 4(f) Evaluation, as required (FHWA deliverables) Section 6(f) Evaluation, as required Traffic Noise Technical Report Hazardous Materials Modified Environmental Site Assessment Community Understanding Technical Memo Prime and Unique Farmlands Technical Memo Right of Way memo Utilities and Railroad Mapping and Permits Requirements Visual Impact Assessment Geologic Technical Report Cumulative Impacts Report Cumulative Impacts Report Existing Transportation Conditions Technical Report (passenger vehicle, freight, bike, pedestrian and transit) Project Administrative Record 			
F. PUBLIC AND AGENCY INVOLVEMENT			
1. Prepare and implement an Agency Coordination Plan (EA)		X	<u> </u>
 2. Public Stakeholder Involvement Plan (EA) Prepare and implement a Stakeholder Involvement Plan specific to the nature of this project. The level of effort included in the plan will be in keeping with the complexity and expected controversy of the project. Coordinate with the CDOT/PM and project team to identify the level of effort to be documented in the plan. NEPA Manual Chapter 7 has additional guidance. At a minimum, the plan should: a. Develop a stakeholder database b. Identify methods for public notification and dissemination of information, such as newsletters, social media, flyers, postcards, web site, press releases, miscellaneous informational materials, etc. c. Identify outreach strategies that comply with Title VI and Limited English Proficiency (LEP) requirements. d. Identify Environmental Justice (EJ) Communities and DIC (disproportionately impacted communities). Create and implement stakeholder engagement activities to reach these communities and gather their input on the project. Coordinate with the CDOT Communications 	C C	X X X	
e. Statistically Valid Community Survey for multi-modal options (Find out public's split in modes of transportation)		X X	

G. NEPA DOCUMENTATION PROCESS		
Develop, coordinate, write, review, conduct QA/QC and finalize the appropriate NEPA document in accordance with CDOT NEPA Manual Chapter 8, as well as		v
the current provisions of the following laws, regulations, and standards.	<u> </u>	X
1. Draft and Final NEPA Document Preparation (EA)		
Assign a team leader qualified to (1) manage the NEPA process, (2) develop a		
schedule for document preparation, printing, review, and comment response, (3)		
will direct the Consultant team in the following tasks in coordination with the CDOT Region, EPB, and FHWA. The CDOT NEPA Manual specifies the number		
of copies to be provided for document review for each phase of the NEPA		
process.		
Use of Geographic Information Systems (GIS) for environmental data is required to be in compliance with CDOT GIS standards. All GIS data shall be provided to		
CDOT in electronic format with the annual updates for the project file.		X
a. Distribute the internal draft NEPA document and relevant technical		Λ
reports for review to a distribution list specified by CDOT. Prepare no		
more than 5 versions of the draft NEPA document and relevant technical		
reports with each version. Provide effort for no more than 2 review		
cycles of the draft NEPA document and relevant technical reports.		
Coordinate and conduct no more than two comment resolution meetings		
for distribution list comments. Respond to comments within a reasonable		
number of working days after received.	С	X
b. Prepare a NEPA document outline for review by CDOT and FHWA.	<u> </u>	İ
Prepare no more than three versions of the outline to be submitted and		
reviewed, with reviews and approvals being conducted by CDOT,		
FHWA, and other appropriate agencies.	С	X
c. For the review cycles, prepare a comment/response matrix for each draft		
NEPA document and relevant technical reports that describe how each		
comment was addressed. This matrix will be distributed with each		
version of the draft document and relevant technical reports that CDOT		
and FHWA review.	С	X
d. Submit the NEPA document to CDOT for signature and routing to		
FHWA for approval.	C	X
e. Draft NEPA Document Distribution, Advertising and Public Review,		
Review and Concurrence, and Public NEPA Document Availability and		
Advertisement.	C	X
f. Create draft and final text for the public Notice of Availability of the		
NEPA document and the date, time and location of the public hearing [if		
appropriate for NEPA document] for placement in all appropriate local		
papers and within the Federal Register [if for an EIS] and provide to the	~	
FHWA Operations Engineer for processing.	С	X
g. Provide an electronic version of the NEPA document and relevant		
technical reports on the CDOT website in PDF, or other read only		W
format.	С	X
h. Make revisions to the final draft NEPA document and relevant technical		
reports. The resulting NEPA document and relevant technical reports		
will be provided to CDOT for distribution and final review, prior to		
preparing the signature copy. Provide certification that all comments		
have been addressed. The Consultant shall submit a signature copy of		
the NEPA document and relevant technical reports to CDOT for signatures and routing to FHWA for approval, and then will provide		
copies of the signed final NEPA document to CDOT.		X
2. Public Meeting for EA		X

Provide the following services, in coordination with the CDOT Region and in			
accordance with Chapter 7 of the NEPA Manual : a. Identify ADA compliant and transit accessible facility for a public			
meeting.		X	
b. Advertise the public hearing/meeting date and location. The following media will be used for advertisement: press releases for newspapers and other media, CDOT website, mailed meeting notices, email meeting notice, social media, and s, door hangers, public displays, community			
newsletters, etc.	С	X	
777		X	
c. Hire translator, or sign language communicator, as needed d. Provide audio/visual equipment and support for presentations, as needed		X	
e. Prepare the graphics/display boards to include, at a minimum, the		Λ	<u> </u>
following features:		X	
i. Purpose of and need for project		X	
ii. Maps showing alternatives		X	
iii. Description of social, environmental and economic impacts		X	
iv. Design features	<u>:</u>	X	<u>†</u>
v. Consistency with federal and local plans	<u>:</u>	X	<u>†</u>
vi. Right-of-way information, acquisition, and construction	<u>:</u>	X	†
vii. Source and amount of funding		X	<u> </u>
viii. Location of recreational resources, Section 6(f) and Section		Λ	<u> </u>
4(f) properties if required		X	
ix. Any other project-specific resource impacts deemed appropriate		X	
x. Mitigation measures that warrant public disclosure or relevance	å	X	
xi. Anticipated project schedule and next steps		X	
xii. How and where the public can provide comments	<u>:</u>	X	†
f. Provide a court reporter (if public hearing) and prepare a certified	<u>:</u>	21	†
transcript of the public hearing within X working days after the public			
hearing/meeting.			N/A
3. Decision Document (FONSI/ROD) Preparation (EA or CatEx)		· · · · · · · · · · · · · · · · · · ·	
There is no guarantee of the outcome of the NEPA process in order to determine next			
steps after an EA and therefore a scope of work cannot be prematurely developed			
for the NEPA decision document. This scope of work and contract will be			
reevaluated once the preliminary EA process is complete and the lead agency has			
made a decision on how to proceed.			
In the event that significant impacts are identified in the EA, the NEPA process would be required to continue the preparation of an EIS rather than a FONSI.			
Continuing to prepare an EIS after completion of an EA is at CDOT's and			
FHWA's discretion and should not be considered part of the initial EA scope of			
work. At this point, a separate Consultant contract would be required, with a new			
scope of work.			
In the event that a decision document is deemed necessary, this contract and scope of			
work would be amended with the concurrence and agreement of both CDOT and			
FHWA (and other applicable agencies). At the conclusion of the public comment			
period, (if the project is determined to have no significant impact, a Finding of No Significant Impact (FONSI)) (if determined to have a significant impact then a			
Record of Decision (ROD)] document may be prepared. In the event a scope of			
work is prepared for a NEPA decision document to be drafted, the following			
services would be addressed in coordination with the Region and EPB:	С	X	
a. Prepare draft NEPA decision document and relevant supporting			1
documentation for incorporating comments received at the public			
hearing/meeting or from the NEPA document public review period.	C	X	

i. Submit draft NEPA decision document, electronically and 5 hard copies using templates when appropriate and relevant supporting documentation to CDOT Region, EPB, and FHWA for 2 reviews.	С	X	
ii. Coordinate and conduct a draft NEPA decision document and relevant supporting documentation review meeting and modify the draft decision document to respond to comments received.			
Provide certification that comments have been addressed. iii. If necessary, re-submit the draft NEPA decision document and relevant supporting documentation for review to ensure that all comments have been made.	C C	X	
iv. If necessary, modify the draft NEPA decision document and relevant supporting documentation to respond to comments received.	С	X	
v. Submit final NEPA decision document and relevant supporting documentation for signature using the signature process outlined in the CDOT NEPA Manual.	С	X	
b. This Scope of Work could be supplemented for additional as-yet unidentified work, if CDOT determines additional work is warranted or needed. In the event that none of the alternatives is selected at the conclusion of the [EA] process, this portion of the scope and contract will be voided.		X	
4. Interchange Modification Reports.			
 a. An Interstate Access Request (IAR) or Minor Interchange Modification Request (MIMR) will be prepared and provided to CDOT and FHWA. The document will need to be approved by both agencies to be considered completed. 			
 All documentation for the 1601 process will need to be prepared and provided to CDOT. CDOT will need to approve documentation before it is considered Completed. 		X	

SECTION 7 PRECONSTRUCTION WORK TASK DESCRIPTIONS

Note: The following activities of communication, consensus building, project team reviews, conceptual design, data gathering, documentation, and formal public notice shall be planned by the Consultant and coordinated with the CDOT PM. The time of their accomplishment may overlap and parallel paths of activity that should be planned to finish the development phase in accordance with the shortest possible schedule. A project plan shall be developed by the Consultant that satisfies the requirements of the project development. This plan must be approved by the Contract Administrator (see Section 2.01) before starting the work. Deliverables can be static reports and products, digital reports and products, and/or GIS data layers. The scope should be specific as to what type of deliverable is expected.

This list establishes the individual task responsibility. Those tasks identified as CDOT/Other should utilize an abbreviation system to indicate whether the task will be completed by CDOT or another agency (i.e. "C" for CDOT and abbreviations as provided below). The consultant shall maintain the ability to perform all work tasks indicated below by an 'X' in the consultant column, in accordance with the forms and conditions contained herein, and the applicable CDOT standards. Where appropriate, mark "N/A" for not applicable items.

*Other Agency Abbreviations:

- A. American Traffic Safety Services Association= ATSSA
- B. Colorado Contractors Association = CCA
- C. Colorado Department of Public Health and Environment = CDPHE
- D. Colorado Water Conservation Board = CWCB
- E. Federal Emergency Management Agency = FEMA
- F. Federal Highway Administration = FHWA
- **G.** Mile High Flood District = MHFD
- H. United States Army of Corps of Engineers = USACE
- I. Other

			.
	C		
	D		N
	О	C	0
	T	0	t
	(n	A
	C	S	р
)	u	р
	/	l	li
	О	t	c
	t	a	a
	h	n	b
	e	t	l
	r		e
	*		
A. PROJECT INITIATION AND CONTINUING REQUIREMENTS			
1. Environmental Mitigation and Requirements			
Ensure that any mitigation commitments within the NEPA documentation are			
incorporated into the project.	C	X	
2. Independent Design Review			
An independent design review shall be performed on any design accomplished by others			
that will be used in this project. A report identifying the results of these reviews shall			
be submitted to the CDOT/PM within one week of the review.		X	
3. Identify Design Criteria		X	

Submit a copy of Appendix B -Specific Design Criteria with the appropriate items completed.	
4. Initiate Survey Arrange Preliminary Field Survey and/or Aerial Survey. CDOT Form 1217a is an outline of a complete survey request and may be used as a guide for completing the survey plan.	X
5. Traffic Control	
Consultant field activities that interfere with traffic operations within existing roadways will require control of traffic. The Consultant shall plan and provide any required traffic control for the survey, testing, or the design process. Traffic control operations will be in accordance with the MUTCD. The proposed Method for Handling Traffic (MHT) must be submitted to the CDOT/PM. Also, certification of the Traffic Control Supervisor as a Worksite Traffic Supervisor by the American Traffic Safety Services Association (ATSSA) or as a TCS (Traffic Control Supervisor) by the Colorado Contractors Association (CCA) shall be required.	X
6. Structure Review Meeting	
While the major structural design work is progressing, the Consultant shall meet periodically with the CDOT Structure Reviewer to review the work. These meetings may be in addition to, or in conjunction with, the Project Progress Meetings. The complexity of the structure shall be considered by the CDOT Structure Reviewer to determine the frequency of review meetings. Other required meetings are described in subsequent sections.	X
7. Initial Submittals	
Submit the following samples to the CDOT/PM for approval:	
An original plan sheet that complies with this scope of work	X
b. Photogrammetric and/or survey data and a drawing or photograph in accordance with the requirements specified in this scope of work	X

Note: No original plan sheets or photogrammetric survey work will be accomplished until satisfactory samples have been received and approved by the CDOT/PM.

B. PROJECT DEVELOPMENT	
1. Survey	
Surveys will be conducted in accordance with the CDOT Survey Manual, the latest	
addendum thereof, and applicable state statutes. The completed survey shall be	
reviewed by the Region survey unit. Two weeks should be provided in the schedule	
to complete the review and sufficient time should be provided to address all	
comments provided by this review. Design shall not proceed until all comments	
resulting from this review have been satisfactorily addressed.	
· ·	X
a. Pre-survey Conference	
A pre-survey conference shall be held. The consultant shall attend the	
Presurvey conference prior to any right of way or survey work	X
b. Survey Data Research	
Research shall be done as per current CDOT manuals	X
c. Project Control Survey:	
i. Locate or Establish HARN Stations	
Project control shall be tied to the nearest Colorado High Accuracy	
Reference Network Station (HARN). CDOT will provide existing	
control information to be verified and expanded upon as necessary by	
the consultant for use on the project.	X
ii. Monumentation	
Materials will be supplied by CDOT. Care is to be taken to install said	
monumentation in locations that are readily usable for the project and	
in a safe location so that they can be utilized throughout construction	X

	(no monumentation shall be set on or near the centerline of the proposed roadway).	
	iii. Local Project Control	
	Survey the required project control (centerline/baselines and elevation reference) as required. Prepare a supplemental control survey diagram showing graphical representation of all monuments used for control. Tabulate coordinates and physical descriptions of all found and set monuments and other physical evidence.	X
d.	Land Survey/Boundary Survey	
	Tie aliquot, property and other land monuments to the control survey. Prepare a Land Survey Control Diagram showing graphical representation of all found aliquot, property and land monuments and their relationship to the project control. Tabulate the coordinates and physical description of all found monuments and other physical evidence.	X
e.	TMOSS (Topographic) Survey	
	Collect the data required to produce a planimetric map and submit in TMOSS format. Features located will include, but not be limited to signs, mailboxes, fences, driveways, curb cuts, curbs, sidewalks, and edges of pavements. Horizontal accuracy shall be as specified for a CDOT class C or D TMOSS survey.	X
f.	Terrain (Relief or Elevation) Survey	
	Collect elevation data and submit in TMOSS format. Natural ground elevations shall be as specified.	X
g.	Utility Survey (ONLY INCLUDE HOURS FOR TASKS NOT COMPLETED IN THE ENVIRONMENTAL SECTION ABOVE [SECTION 6]). Locate utility poles, manholes, valves, pedestals, guy wires, and other visible utility features. Survey underground utilities as marked by the utility companies. Determine invert elevations of manholes and vaults and survey the locations of utilities exposed by "potholing".	X
h.	Hydraulic Survey	71
11.	Locate existing bridge limits, bridge high chords and low girders, culvert invert elevations and locations and sizes, storm sewers, inlets, vaults, manholes, PWQ structures, and determine invert and rim elevations and sizes and materials. Accomplish existing drainage site surveys for designated culverts and bridges in accordance with the Drainage Design Manual. Prepare a topographic survey of the waterway, overbanks, and floodplain areas upstream and downstream to limits determined by the Region Hydraulic Engineer or his/her designee. Incorporate statewide LiDAR data from State of Colorado resources whenever available at	
	www.coloradohazardmapping.com or https://geodata.co.gov/.	X
i.	Material Sources	v
	Survey designated material sources as specified.	X
J.	Supplemental Surveying: As required and specifically requested.	X
k.	Survey Report: Prepare a Survey Report as required in the Survey Manual.	X
1.	Photogrammetry	X
1.	i. Camera Calibration Report	X
	ii. Flight Plan	X
	iii. Flight	X
	iv. Contact Prints	X
	v. Negatives	X
	vi. Enlargements	X
	vii. Photo Index	X

viii. Supi	plemental Survey (wing points)	-	X
	Reduction	İ	<u>.</u>
	a) Topographic Contours		
	b) Planimetric (Topography)		X
x. Map	Compilation		
	a) Index Maps		
	b) Finished Maps		X
m. Accuracy			
	to be performed on a regular basis throughout the project by the		
consultar			X
	by Professional Land Surveyor	·	
	racy tests are to be reviewed by the PLS in responsible charge for		
	ct, and submitted to the project engineer and made part of the		
	ecords. Further review of all aspects of the field and office work		
	be the responsibility of the PLS in responsible charge.		X
C. PRELIMINAR			
1. Traffic Engi			X
	ocations with "potential for accident reduction map" and or traffic	<u>i</u>	21
	as analysis and or the safety assessment report as provided by		
	o determine which safety improvements will be incorporated into		
the proje			X
	the proposed project design with the traffic projection data	·····	X
	end the appropriate geometry (i.e., number of lanes, auxiliary lanes,	<u>i</u>	21
	engths, weaving distances, etc.) in accordance with the current		
	of Highway Capacity Manual.		X
	osed design shall be reviewed to ensure compatibility with existing		21
	procedures throughout the preliminary roadway design process		X
	ic data appropriate to the anticipated construction timing in		
	ng detour alternatives.		X
	the total ESAL for the design life and submit to the CDOT/PM for		
the naver	nent design.		X
	traffic data and recommendations to the CDOT/PM for review.	·····	
g. Sublint ti	to the CDO 1/1 Wi for leview.		
			X
h Prepare ar	nd provide pavement marking plans and major signing plans.		
ii. Trepure un	ta provide pavement marking plans and major signing plans.		X
2. Intelligent T	ransportation Systems (ITS)		
	ate, locate, and Design existing ITS device infrastructure resets,		
	ents, and/or replacements as necessary to fit within the proposed		
infrastru			
b. Coordina	ate and Design designed ITS device infrastructure as necessary to fit		
	e designed features.		
	network and splicing diagrams for proposed work.		
			X
3. Information	Management		
	ate, locate and design device hardware and software infrastructure		
•	y for vehicle to vehicle and vehicle to infrastructure technology in		
	ce with, but not limited to the CO 7 Corridor Technology		
Deploym			
	coordination, and implementation of a data sharing platform.		
	ith development of Intergovernmental Agreements (IGA).	C	X
	ineering Analysis (SEA)		
	ate, provide and prepare necessary materials for the execution of		
SEA doc	umentation	<u>i</u>	X

b	A full system engineering analysis will be required following the CDOT	
	process.	
	Other work as necessary to support the SEA.	
d.	ITS and Information Management Technology will need to be included in	
	SEA.	
5. Mat	erials Engineering	
	eliminary soil investigation should be conducted.	X
	Determine test hole locations (horizontal and vertical) and coordinate with	
:	the CDOT/PM.	X
	Collect soil samples and test for:	- 21
:	i. Classification	
•	ii. Moisture – Density Relationship	
:	iii. Resistance Value	
•	iv. Corrosiveness – Note locations of high corrosiveness with	
	recommendations; see CDOT pipe material selection policy.	
	v. Bearing Capacity	
:	vi. Time Rate of Consolidation	
:	vii. Slope Stability	X
	Prepare and submit a soils investigation report.	X
	Prepare and submit pipe material selection report.	X
!	ement	
·	Pavement Rehabilitation	
•	This section applies if the project includes existing pavement that is	
	incorporated in the design for continued utilization.	X
!	Determine the equivalent Design Traffic (18k ESAL) that the existing	Α
'	pavement can carry	X
		X
ļ	ii. Estimate the 18k ESAL's experienced by the existing pavement. iii. Obtain the projected 18k ESAL for rehabilitated pavement design	Λ
J	period.	X
		Λ
J	iv. Perform a distress survey a) Determine the types of distress present in the pavement	
	b) Determine the types of distress present in the pavement b) Determine the extent of each distress type	
	c) Develop a distress map for the existing pavement	
	d) Determine the causes of the existing distress utilizing tests and	
	required and analyses.	
	e) Determine the drainage conditions of the existing surface and	
	subsurface	X
,	v. Investigate the existing pavement structure	- 23
	a) Subgrade: soil classifications, moisture/density relationship,	
	resistance value and corrosiveness	
	b) Base: thickness, gradation, plasticity index, liquid limit,	
	resistance value, strength coefficient	
	c) Pavement: thickness, strength coefficient	X
İ	vi. Perform deflection testing to obtain the following:	23
	a) Deflection profile	
	b) Maximum deflection	
	c) Deflection basin	
	d) Differential deflections at transverse joints for portland cement	
	concrete pavement (pccp)	
	e) In place determination of the appropriate modulus for each layer	
	and subgrade	X
	vii. Determine the remaining load carrying capacity from the above data.	- 23
	Design the feasible alternatives for the required rehabilitation (and	
		X
	widening if appropriate) utilizing the above investigations and test	X

results. The design of the feasible alternatives shall be checked against the following:		
a) The basic cause of distress which shall be corrected		
b) Effect on the rate of future deterioration		
c) Effect on surface characteristics		
e) Effect on surface characteristics		
Where appropriate, any new pavement widening shall be included in the analysis.		
b. New Pavement Structure		
The feasible alternatives of new pavement structure shall be designed		
utilizing procedures accepted by the CDOT/PM. New pavement designs for		
widening shall be compatible with adjacent rehabilitated existing pavement.	X	
c. Pavement Justification	X	
i. Basic factors:	21	
a) Desired life expectancy (obtain design life from CDOT).		
b) Required maintenance activities intervals.		
c) Basis for performance life.	X	
ii. Analyze life cycle cost of the selected alternatives	Α :	
a) Perform analysis with unit and maintenance costs from CDOT.		
Determine present worth and annual costs in accordance with the		
procedures in the CDOT Pavement Design Guide.		
b) Compare alternatives over the same life span.		
c) Recommend the pavement structure and provide the basis for the		
recommendations.	X	
	Λ	
d. Pavement Design Report		
Include all the above tests, investigations, analyses, and calculations	X	
performed. Submit to the CDOT/PM for acceptance.	Λ	

7. Existing S	Structures and Foundation	
a. Existi	ng bridge condition investigation	
	mine condition of existing bridge deck, superstructure and substructure	
mater	ial as required.	X
	dation Investigation Report	X
	repare a Foundation Investigation Request showing requested test hole	
	ocations.	X
	ormulate drilling pattern, perform the necessary subsurface	
	envestigation and collect samples as required.	X
	erform the appropriate laboratory tests and analyze the data.	21
	Determine strength, allowable bearing capacity and corrosiveness of	
	oundation material.	X
!·····	erform lateral analyses (deformation, moment, and shear) for the	
	aissons and/or piles which are subjected to lateral loadings. This may	
	e a computer analysis which will consider the group effect and	
	election of the soil parameters.	X
	f appropriate, a pile driving analysis using a wave equation will be	Λ
	ccomplished.	X
	ubmit the Foundation Investigation Report to the CDOT/PM for	Λ
		X
1	pproval.	Λ
	repare engineering geology plan sheet and copies of the Foundation	
	nvestigation Report foundation report with recommendations for type,	
	ize, and tip (bottom) elevation of the required foundation. Specify if	
	re-drilling, pile tip, casing, dewatering, etc., are needed for foundation	v
ļ	onstruction.	X
	f requested, perform a gradation analysis of the streambed/waterway	
	ative material using a sieve analysis, Wolman Count, or other	
	cceptable method as directed by the Region Hydraulic Engineer or	77
ļ	is/her designee.	X
	y/Hydraulic Engineering	
·	Collection and Hydrology	X
	stablish drainage basin data: delineate and determine size, waterway	
	eometrics, vegetation cover, and land use.	X
ii. C	Collect historical data: research flood history and previous designs in	
tl	ne project proximity; obtain data from other sources (e.g., MHFD,	
C	WCB, CDOT Maintenance, and local residents).	X
iii. C	Complete a project site visit to evaluate channel/overbank roughness	
:	oefficients, channel stability, vegetation, condition/adequacy of	
	xisting structures, Ordinary High Water, allowable high water, etc.	
	Occument the site visit with photos.	X
	elect a design storm frequency based on the established criteria.	X
	Complete a hydrological analysis using existing studies or approved	
	nethods.	X
	erform a risk analysis.	X
b. Hydra		X
	Complete preliminary design of minor drainage structures:	
a a		
a	hydraulic design. Identify locations by highway station or	
L.	coordinates, as appropriate.	
b	,	
c	, 1	
1	encountered Assess abugaion and compagion levels based on CDOT Dine	
d	, , , , , , , , , , , , , , , , , , , ,	v
	Material Selection Policy.	X

e) Prepare preliminary structure cross-sections and determine		
e) Prepare preliminary structure cross-sections and determine elevations, flow lines, slopes and lengths of the structures.		
f) Present initial designs of any necessary deck drainage or other		
drainage off the structure.		
ii. Complete preliminary design of major drainage structures:		
a) Complete hydraulic analysis and water surface profiles.		
b) Determine required hydraulic size/skew of major		
structures/channels		
c) Determine minimum low chord elevation per CDOT criteria		
d) Determine design storm and 500-year water surface elevations.		
e) Determine scour for design storm, the 500-year event, incipient		
overtopping condition, and maximum scour-inducing storm (if		
applicable).		
f) Assess channel erosion protection for structures.		
g) Present initial designs of any necessary deck drainage or other		
drainage off the structure.	X	
iii. Determine if existing PWQ CMs are compliant with CDOT's current		
MS4 Permit requirements. Complete preliminary design for new		
Permanent Water Quality Control Measures (PWQ CMs) and outlet		
structures with details as needed. Adequate detail should be included in		
the FIR construction plan set if FIR-level decisions are required with		
respect to right-of-way, easements, maintenance, etc. to move to final	377	
design.	X	
jjj. If required, identify and assist CDOT in coordinating potential funding	v	
participation of local, state, and/or federal agencies.	X	
c. Prepare preliminary construction plans that include:	Λ	
i. Drainage Plan Sheetsii. Drainage Detail Sheets as needed		
ii. Drainage Detail Sheets as needed iii. Hydraulic Information Sheets as needed	X	
d. Prepare a Preliminary Hydraulics Report or Preliminary Drainage Report in	Λ	
accordance with the CDOT Drainage Design Manual		
i. Introduction, Hydrology, Existing Structures and Design Discussion		
sections should be close to final at this level. Design Discussion		
should include CDOT and local criteria the project intends to meet.		
ii. Recommended design should be preliminary at this level and progress		
through final design.		
iii. All design assumptions and related design decisions shall be		
documented.		
iv. The Appendix shall contain:		
a) Drainage basin maps		
b) Hydrology/hydraulic worksheets		
c) Drainage construction plan sheets.		
d) CDOT pipe material selection documentation	7.7	
e) Permanent Water Quality report and PWQ worksheets	X	
e. Perform internal QA/QC prior to submission to CDOT.	X	
9. Floodplain Assessment	<u> </u>	
a. Identify location of regulatory floodplains and floodways published by		
FEMA and local agencies, and assess impacts of planned changes to those	V	
boundaries from CDOT activities or planned map revisions by others.	X	
b. Add information to environmental resource mapping of existing conditions	X	
c. Determine the adverse impacts of each alternative with respect to the base		
flood elevation (BFE), floodway boundary, and local drainage. This must	v	
include the impacts of construction and other "temporary" activities.	X	
 d. Analyze impacts and develop possible actions to mitigate for the adverse impacts, then coordinate with roadway and structural designers. 	X	
impacts, then coordinate with roadway and structural designers.	. Λ	

e. Analyze the impa	cts and mitigation. Included in the analysis will be a		
	significant impacts due to:	X	
i) Single comm	unity access routes.		
ii) Risk for socia	l or economic losses due to flooding		
iii) Alteration of	beneficial floodplain values.		
iv) Recommend	preparation of a local floodplain development permit for		
all work in flo	podplains and floodways, as required by state and federal		
law.			
v) Show all grou	and survey point elevations in the same vertical datum		
	the current effective FIRM.		
vi) Add notes to	indicate the waterway name, jurisdiction and community		
	l number, date of current effective information, a		
	ribing which local code requires permits, a sentence for		
	d no rise compliance, and a note recognizing that		
	occur outside the mapped Special Flood Hazard Area		
(SFHA).		X	
	ain Information Sheet for the final approved plan set.	X	
	arly label the current effective 100-yr floodplain and		
	and the 500-year floodplain (as applicable).		
	arly label all cross sections and BFE lines published on		
,	fective FIRM (note; all elevations must be reported in the		
	datum identified on the current effective FIRM).		
	arly label any fluvial hazards, buffer zones or erosion		
management			
_	its of disturbance for all permanent and temporary		
	l label as such.		
	and survey point elevations in the same vertical datum		
	the current effective FIRM.		
	:		
	indicate the waterway name, jurisdiction and community		
	l number, date of current effective information, a		
	ribing which local code requires permits, a sentence for		
	d no rise compliance, and a note recognizing that		
	occur outside the SFHA.		
	tions of approval from the local agency to the notes,		
	as-built survey and P.L.S. & P.E. re-certification		
requirements.		37	
D D 11 1	entifying any 625 Survey specials.	X	
9 1	nary Floodplain Report or Memo as outlined in the CDOT		
•••••••••••••••••••••••••••••••••••••••	ed by the Region Hydraulic Engineer or his/her designee.	X	
10. Environmental – Wa			
a. Storm Water Man			
Initiate a Storm Water	Management Plan in accordance with: C	X	
	parate Storm Sewer Systems (MS4)		
	nstruction Discharge Permit System requirements		
	ion Control and Storm Water Quality Guide		
iv) Local agency	SWMP/GESC/EC requirements		
	dard Specifications		
vi) CDOT Standa			
vii) Other appropr	riate documents	X	
b. Topsoil sampling,		X	
	mber for revegetation units required by coordinating	v	
with SWMP of	designer and design team. Number of samples: 2 per mile	X	

	ii) Conduct topsoil sampling and send samples to laboratory for nutrient	1		
	11) Conduct topsoil sampling and send samples to laboratory for nutrient testing; refer to <i>topsoil sampling procedure</i> for laboratory testing			
	requirements.			
	iii) Incorporate topsoil amendments into the SWMP.			
c.	Vegetative Transects	С	X	
:				
	i) i. Determine number of revegetation units required by coordinating			
	with SWMP designer and Environmental Specialist. Number of			
	transects: one per 5 acres			
	ii) ii. Conduct <u>vegetation transect(s)</u> to determine existing vegetative			
	percent cover as required for each vegetation unit as determined in the SWMP prior to construction disturbance.			
	iii) iii. Document transect location(s) and percent cover(s) onto an aerial map. Place map and photographs into Tab 17.		X	
1			Λ	
d.	Prepare preliminary Permanent Water Quality (PWQ) plans in conjunction with Section 7.C.5.b.iii of this document.		X	
			Λ	
	i) Determine PWQ requirements (local agency MS4 requirements,			
	CDOT requirements, etc.)			
	ii) Develop PWQ alternatives that will meet CDOT and local agency			
	MS4 requirements iii) Identify eight of year requirements and utility imports for alternatives			
	iii) Identify right-of-way requirements and utility impacts for alternatives			
	iv) Identify all entities and include memo which details responsibilities for existing facility maintenance and operations and future facility			
	maintenance and operation. Create draft Maintenance and permanent			
	water quality maintenance scope of work and map exhibits for IGA's			
	with CDOT, MHFD and Local Agencies.			
	v) Other appropriate documents		X	
	Prepare preliminary permanent water quality report as an appendix to the		Λ	
e.	Hydraulic Design Report to include PWQ Evaluation and Tracking Forms,			
	cost estimate for PWQ CMs, etc.		X	
f.	Conduct a PWQ meeting after scoping and just prior to FIR to discuss		Λ	
1.	alternatives with CDOT PWQ Specialist, Hydraulics Engineer, Local			
	Agency, MHFD, and Project manager.	С	X	
~	Perform internal QA/QC prior to submittal to CDOT.		X	
g.	Draft and finalize IGA for PWQ facilities with local agencies for		Λ	
11.	construction, operations and maintenance.	С	X	
11 1142	lities		Λ	
111 041				
а.	Utility Coordination			
	i Location Maps Obtain utility location mans from the Utility Companies which identify			
	Obtain utility location maps from the Utility Companies which identify			
	utility features in the project area. Requests and receipt of maps will be coordinated with the Region Utility Engineer via copies of request and			
	transmittal letters.		X	
			Λ	
	ii Reviews and Investigations Conduct field reviews and utility investigations with the Pegion Utility			
	Conduct field reviews and utility investigations with the Region Utility			
	Engineer and Utility companies, as required, to ensure correct horizontal and vertical utility data. When possible this will be done			
	utilizing non-destructive investigative techniques. The horizontal and			
	vertical locations will be shown in the FIR plans and cross sections.			
	When "potholing" is required, the Consultant shall be responsible for			
	all necessary excavations.		X	
			X	
	iv Relocation Recommendations		X	

	<u>-</u>
Submit necessary information for the relocation or adjustments of	
affected utilities to the Region Utility Engineer. The Region Utility	
Engineer will process the required agreements.	
v Ditch Company Coordination	
Contact ditch companies through the Region Utility Engineer to coordinate	
ditch requirements and restrictions. Develop the plans for the necessary	
irrigation structures and submit to the Region Utility Engineer for Ditch	
Company review.	
vi. Provide an inventory of addresses associated with utility meters within	
the project.	
vii. Contact local municipalities to establish addresses for new metered	X
services, coordinating with the CDOT Utility Account Coordinators to	X
document new meters.	X
12. Subsurface Utility Engineering	
Create and provide a set of SUE plans that adheres to ASCE 38-22 standards and	
CRS 9-1.5. This includes an attempt at Quality Level-B designations of all	
utilities within the SUE required area, and Quality Level-A test holes where	
necessary. Create and provide utility conflict matrix and test hole log as	
appropriate.	
	X
13. Roadway Design and Roadside Development	1.
Coordinate all design activities with required CDOT specialty units and other outside	
entities.	
	v
a. Roadway Design	X
i) Input, check, and plot survey data	X
ii) Verify that a project specific coordinate system approved by CDOT is	
used to identify the horizontal locations of key points. The coordinate	***
systems used for roadway design and ROW shall be compatible.	X
iii) Input and check horizontal and vertical alignments against all design	
criteria. Necessary variances and/or design decisions will be identified	
with justification and concurrence by CDOT & FHWA.	X
iv) Provide alignments, toes of slope and pertinent design features,	
including permanent and temporary impacts, to the ROW, Utility and	
Environmental Managers.	X
v) Plot/develop all required information on the plans in accordance with all	
applicable CDOT policies and procedures.	X
vi) Using current approved CDOT software, generate a 3 dimensional	
design model and produce preliminary quantities	X
b. Roadside Development:	
For roadside items including but not limited to, guardrails, delineators,	
ditches, PWQ CMs, landscaping, sprinkler systems, sound barriers, bike	
paths, sidewalks, lighting, curb ramps, truck escape ramps, and rest areas	
provide the following layouts in the plans:	X
i) Critical locations in the plans for irrigation sleeves and other utility	
conduits underneath the proposed roadways.	X
	Λ
	X
(SWMP).	Λ
14. Right-of-Way	
The following work shall be done by, or under the immediate supervision of, a	
Professional Land Surveyor (PLS). The following work may be included as part of a	**
Surveying contract or part of a Right-of-Way plans preparation contract.	X
a. Research	X

X	
X	
Λ	
v	
Λ	
v	
X	
X	
X	
X	
X	
X	
X	
21	
v	
Λ	
v	
Α	
X	
X	
X	
	X X X X X X X X X X X X X X X X X X X

xii) Label all monuments found with description of monument and project	
coordinates (from Control Survey Diagram)	X
xiii) Show improvements and topography within the ownerships and existing	
access to the street/county road system.	X
xiv) Number ownerships alternately as they occur along the centerline from	
south to north or west to east in the same direction as the stationing.	
Show current names of owners and lessees	X
xv) Calculate the total area of all ownerships affected, including coordinates	
of all property corners. Deduct areas for existing road Rights-of-Way.	
Bearings and distances do not need to be shown on 1" = 1 mile	
abbreviated OWNERSHIP MAPS	X
xvi) Different land uses within a property should be cross-hatched or shaded.	X
;	Α
	v
number and name of Professional Land Surveyor supervising the work	X
xviii) Transmit finished reproducible OWNERSHIP MAP, electronic	
drawing files, and Memoranda of Ownership to CDOT along with all	
calculations, field notes, and supporting data. The OWNERSHIP MAP	
will include a copy of the control and monumentation sheet	X
15. Major Structural Design	
Major structures are bridges and culverts with a total length greater than twenty feet or	
retaining walls with a maximum exposed height at any section of four feet or greater.	
This length is measured along centerline of roadway for bridges and culverts, and	
along the top of wall for retaining walls. Overhead sign structures (sign bridges,	
cantilevers, and butterflies extending over traffic) are also major structures, but are	
exempt from the structure preliminary design activity defined here. The CDOT	
Structure Reviewer will participate in coordinating this activity.	X
a. Structural Data Collection	X
i) Obtain the structure site data. The following data, as applicable, shall be	
collected: (Typical roadway section, roadway plan and profile sheets	
showing all alignment data, topography, utilities, preliminary design	
plan) Right-of-Way restrictions, preliminary hydraulics and geology	
information, environmental constraints, lighting requirements, guardrail	
types, recommendations for structure type, and architectural	
recommendations.	X
	Λ
ii) Obtain data on existing structures. When applicable, collect items such	
as existing plans, inspection reports, structure ratings, foundation	
information, and shop drawings. A field investigation of existing	77
structures will be made with notification to the Resident Engineer.	X
b. Structure Selection and Layout	X
i) Review the structure site data to determine the requirements that will	
control the structure size, layout, type, and rehabilitation alternatives.	
On a continuing basis, provide support data and recommendations as	
necessary to finalize the structure site data.	X
ii) Determine the structure layout alternatives for all structures that will be	
impacted or needed for the preferred alternative. For 88th avenue	
bridge and the potential pedestrian underpass and/or overpass;	
determine the structure length, width, and span configurations that	
satisfy all horizontal and vertical clearance criteria. For walls, determine	
the necessary top and bottom of wall profiles.	X
	Λ
iii) Determine the structure type alternatives. For bridges, consider precast	
and cast-in-place concrete and steel superstructures and determine the	v
spans and depths for each. For walls, determine the feasible wall types.	X
iv) Determine the foundation alternatives. Consider piles, drilled caissons,	
spread footings, and mechanically stabilized earth foundations based on geology information from existing structures and early estimates from	X

the project geologist. To obtain supporting information, initiate the foundation investigation as early as possible during the preliminary design phase. v) Determine the rehabilitation alternatives. Continued use of all or parts of existing structures shall be considered as applicable. The condition of existing structures shall be investigated and reported. Determine the modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. x) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout, with supporting drawings, tables, and discussion, provide for the following:
design phase. v) Determine the rehabilitation alternatives. Continued use of all or parts of existing structures shall be considered as applicable. The condition of existing structures shall be investigated and reported. Determine the modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
v) Determine the rehabilitation alternatives. Continued use of all or parts of existing structures shall be considered as applicable. The condition of existing structures shall be investigated and reported. Determine the modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
of existing structures shall be considered as applicable. The condition of existing structures shall be investigated and reported. Determine the modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. Vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. Vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Viii) Evaluate the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X X X X X X X X X X X X X
existing structures shall be investigated and reported. Determine the modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. Vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. Vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Viii) Evaluate the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. Xix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
modifications and rehabilitation necessary to use all or parts of existing structures and the associated costs. vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. X vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Stablish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
structures and the associated costs. vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. X vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. X viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. C. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
vi) Develop the staged construction phasing plan, as necessary for traffic control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. X Vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. X Viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
control and detours, in conjunction with the parties performing the roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. X Xii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Xiii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. Xix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. C. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
roadway design and traffic control plan. The impact of staged construction on the structure alternatives shall be considered and reported on. X X Xii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. X Xiii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. C. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
construction on the structure alternatives shall be considered and reported on. X X X X X X X X X X X X X
reported on. Vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X X ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. C. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
vii) Compute preliminary quantities and preliminary cost estimates as necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. X viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. X ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
necessary to evaluate and compare the structure layout, type, and rehabilitation alternatives. Viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
rehabilitation alternatives. X Viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
viii) Evaluate the structure alternatives. Establish the criteria for evaluating and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
and comparing the structure alternatives that, in addition to cost, encompass all aspects of the project's objectives. Based on these criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
criteria, select the optimum structure layout, type, and rehabilitation alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
alternative, as applicable, for recommendation to CDOT. ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
ix) Prepare preliminary general layout for the recommended structure. Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
Prepare structure layouts in accordance with current standards. Special detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
detail drawings and a detailed preliminary cost estimate shall accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. C. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
accompany the general layout. The special detail drawings shall include the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
the architectural treatment. Perform an independent design and detail check of the general layout. c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
check of the general layout. X c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
c. Structure Selection Report Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
Prepare a structure selection report to document, and obtain approval for, the structure preliminary design. By means of the structure general layout,
the structure preliminary design. By means of the structure general layout,
the structure preliminary design. By means of the structure general layout,
with supporting drawings, tables, and discussion, provide for the following: X
11 0 0 , , , , , , , , , , , , , , , , ,
i) Summarize the structure site data used to select and layout the
structures. Include the following:
a) Existing structure data, including sufficiency rating and whether
or not the structure is on the "select list".
b) Project site plan
c) Roadway vertical and horizontal alignments and cross sections at
the structure
d) Construction phasing
e) Utilities on, below, and adjacent to the structure
f) Hydraulics:
g) Channel size and skew, design year frequency, minimum low
girder elevation, design year and 500-year high water elevations,
estimated design year and 500 year scour profiles, and channel
erosion protection
h) Preliminary geology information for structure foundation
i) Architectural requirements X
ii) Report on the structure selection and layout process. Include the
following:
a) Discuss the structure layout, type, and rehabilitation alternatives
considered
• • • • • • • • • • • • • • • • • • • •
b) Define the criteria used to evaluate the structure alternatives and
b) Define the criteria used to evaluate the structure alternatives and how the recommended structure was selected

layout. Allow approximately two weeks for review of the structure selection report. The associated general layout, with the revisions required by the CDOT review, will be included in the FIR plans. The structure selection report, with the associated general layout, must be accepted in writing by CDOT prior to the commencement of further design activities. d. Foundation investigation Request Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction plansing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include at title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drai			····· ·
selection report. The associated general layout, with the revisions required by the CDOT review, will be included in the FIR plans. The structure selection report, with the associated general layout, must be accepted in writing by CDOT prior to the commencement of further design activities. d. Foundation Investigation Request Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing truffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans. d. The FIR plans shall comply with CDOT requirements and shall include at title sheet, typical sections, general notes, plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary ca	iii) Obtain acceptance by CDOT on the recommended structure and its		
required by the CDOT review, will be included in the FIR plans. The structure selection report, with the associated general layout, must be accepted in writing by CDOT prior to the commencement of further design activities. d. Foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans based on estimated quantities. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include at title sheet, typical sections, general notes, plan'profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing to Wir, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary carthwork (plotted cross sections at critical points			
structure selection report, with the associated general layout, must be accepted in writing by CDOT prior to the commencement of further design activities. d. Foundation Investigation Request Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction Phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include at its esheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following tierns will be mandatory for the FIR plans: a) Preliminary earthwork (plotned cross se			
accepted in writing by CDOT prior to the commencement of further design activities. d. Foundation Investigation Request Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction plan shell be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans shall occupilly with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Prit data (f'required) e) Soll profile and stabilizatio			
design activities. d. Foundation Investigation Request Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction Phasing Plan A construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (f required) e) Soil profile and st			
d. Foundation Investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction phasing Plan A construction planing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, profile gheats will include all existing topography, survey alignments, profile sheets will include all existing topography, survey alignments, profile sheets will include all existing topography, survey alignments, profile sheets will include all existing topography, survey alignments, profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets, and preliminary alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary trainage design notes, inc	accepted in writing by CDOT prior to the commencement of further		
Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction fall the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (If required) e) Soil profile and sta	design activities.	C	X
Initiate the foundation investigation as early in the preliminary design phase as is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction fall the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (If required) e) Soil profile and sta	d. Foundation Investigation Request		
is practical. On plan sheets showing the project control line, its stations and coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (If required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical pl			
coordinates, utilities, identify the test holes needed and submit them to the project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing Plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway remplate and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (fi required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile I inch = 20 feet e. Th			
project geologist. The available general layout information for the new structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Cach points c) Proposed Right-of-Way d) Pit data (i) required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW			
structure shall be included in the investigation request. 16. Construction Phasing Plan A construction phasing Plan A construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections I inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary traffic control p			
A construction Phasing Plan A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Cordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing prography, survey alignments, projected alignments, profile grades, ground line, existing pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) i) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary treview prior t			X
A construction phasing plan shall be developed for all projects which integrates the construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (deteours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) i) Typical pl			
construction of all the project work elements into a practical and feasible sequence. This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (f required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet FIR plan reproduction not to exceed 5 of sets h. The pelanish shall be submitted to the CDOT/PM for a preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
This plan shall accommodate the existing traffic movements during construction (detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (frequired) e) Soil profile and stabilization data f) Structure general layouts (fi applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set			
(detours). A preliminary traffic control plan will also be developed which will be compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets X h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set			
compatible with the phasing plan. 17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary traffic control plan with proposed detours will be included in the FIR plan set The plans plan production not to exceed 5 of sets A the preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set			
17. Preparation for the Field Inspection Review (FIR) a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) The Tollo Feet (Rural) c) Intersections I inch = 20 feet L The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR plan reproduction not to exceed 5 of sets L The plans shall be submitted to the CDOT/PM for a preliminary traffic control plan with proposed detours will be included in the FIR plan set X			v
a. Coordinate, complete, and compile the plan inputs from other branches: materials, hydraulies, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile I inch = 50 Feet (Urban) b) I inch = 100 Feet (Rural) c) Intersections I inch = 50 Feet (Urban) c) Intersections I inch = 20 feet The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			Λ
materials, hydraulics, traffic, right-of-way, environmental and water quality, and Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (frequired) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections I inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			<u>.</u>
Staff Bridge. b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
b. If a major structure is included in the project, including a PWQ CM, a general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Carch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
general layout (which has been accepted by CDOT) will be included in the FIR plans. c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X		С	X
c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, profeeted alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet c. The ROW ownership map shall be included in the FIR plan set X f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
c. Prepare the preliminary cost estimate for the work described in the FIR plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x e. The ROW ownership map shall be included in the FIR plan set x f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR x g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set			
plans based on estimated quantities. d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x e. The ROW ownership map shall be included in the FIR plan set x f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR y g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set x	plans.		X
d. The FIR plans shall comply with CDOT requirements and shall include a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set X g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X	c. Prepare the preliminary cost estimate for the work described in the FIR		
a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X	plans based on estimated quantities.		X
a title sheet, typical sections, general notes, plan/profile sheets, and preliminary layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. c. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X	d. The FIR plans shall comply with CDOT requirements and shall include		
layouts of interchanges/intersections. The plan/profile sheets will include all existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet X c. The ROW ownership map shall be included in the FIR plan set X f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR y g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
existing topography, survey alignments, projected alignments, profile grades, ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
ground line, existing ROW, rough structure notes (preliminary drainage design notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
notes, including pipes, inlets, ditches and channels), and existing utility locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
locations. i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. e. The ROW ownership map shall be included in the FIR plan set x f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR x g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
i) The following items will be mandatory for the FIR plans: a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) x) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			X
a) Preliminary earthwork (plotted cross sections at critical points with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet X e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR S g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X	<u> </u>		
with roadway template and existing utility lines at known or estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) Xii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
estimated depths) b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet X e. The ROW ownership map shall be included in the FIR plan set T, The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
b) Catch points c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR S. TR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
c) Proposed Right-of-Way d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet X e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
d) Pit data (if required) e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X	, 1		
e) Soil profile and stabilization data f) Structure general layouts (if applicable) X ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
f) Structure general layouts (if applicable) ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet x. e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
ii) Typical plan sheet scales will be as follows: a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			v
a) Plan and Profile 1 inch = 50 Feet (Urban) b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet E. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			Λ
b) 1 inch = 100 Feet (Rural) c) Intersections 1 inch = 20 feet X e. The ROW ownership map shall be included in the FIR plan set X f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR X g. FIR plan reproduction not to exceed 5 of sets X h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
c) Intersections 1 inch = 20 feet X e. The ROW ownership map shall be included in the FIR plan set X f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR X g. FIR plan reproduction not to exceed 5 of sets X h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
e. The ROW ownership map shall be included in the FIR plan set f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			v
f. The plans shall be submitted to the CDOT/PM for a preliminary review prior to the FIR X g. FIR plan reproduction not to exceed 5 of sets X h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
prior to the FIR g. FIR plan reproduction not to exceed 5 of sets h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			X
g. FIR plan reproduction not to exceed 5 of sets X h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			
h. The preliminary construction phasing including preliminary traffic control plan with proposed detours will be included in the FIR plan set X			X
plan with proposed detours will be included in the FIR plan set X	g. FIR plan reproduction not to exceed 5 of sets		X
plan with proposed detours will be included in the FIR plan set X	h. The preliminary construction phasing including preliminary traffic control		
			X
i. CDOT form 1048 – project scoping procedures completion checklist X	i. CDOT form 1048 – project scoping procedures completion checklist		X

18. Field Inspection Review	~	3 7
a. Attend the FIR	С	X
b. The FIR meeting minutes shall be prepared by the C/PM, approved by the CDOT/PM, and distributed as directed	С	X
c. The FIR original plan sheets shall be revised/corrected in accordance with the		
FIR meeting comments within thirty (30) working days		Χ
d. Design decisions concerning questions raised by the FIR will be resolved in cooperation with the CDOT/PM. The C/PM shall document the decision and		
transmit the documentation to the CDOT/PM for approval.	С	X
e. A list of all deviations from standard design criteria along with the written		
justification for each one shall be submitted to the CDOT/PM		Χ
19. Post-FIR Revisions		
The Consultant shall complete the revisions required by the FIR before this phase of work		
is considered to be complete		X
a. Update project schedule		X
b. Coordinate activities		X
c. Finalize design decisions, variances, justification process, and traffic signal		2 1
warrants		X
		Λ.
D. FINAL DESIGN		37
1. Traffic Engineering		X
Prepare and provide permanent signing/pavement marking plans. Will		3 .7
include sign details and overhead sign elevation plans.		X
Signalized intersections:		X
i) Prepare and provide the signal warrant study		X
ii) Prepare plan sheet with intersection condition diagrams and required		
traffic signal design and forward to appropriate agency. Prepare 1 inch		
to 20-foot scale intersection plan sheet for each intersection which will		
have a traffic signal designed for it.		X
iii) Prepare and provide the construction traffic control plans and quantities		X
iv) Ramp meter plans sheets. Prepare 1 inch to 20-foot scale intersection		
plan sheet for each intersection which will have a ramp meter designed for it.		X
 v) For all proposed signal and ramp meter locations an one line diagram and fiber connection plan will be needed. 		X
2. Intelligent Transportation Systems (ITS)		
Coordinate, locate, and Design existing ITS device infrastructure resets, adjustments, and/or replacements as necessary to fit within the proposed infrastructure.		
Coordinate and Design designed ITS device infrastructure as necessary to fit within the designed features.		
Generate network and splicing diagrams for proposed work.		X
3. Systems Engineering Analysis (SEA)		
Provide necessary materials for the execution of SEA documentation.		
Other work as necessary to support the SEA.		X
4. Materials Engineering		X
Finalize and provide the stabilization plan/pavement design report.		X
Finalize geotechnical considerations and incorporate them into the plans.		X
i) Rock fall		
1) 100K 1011		
ii) Rock cut		
	:	:

iii) Landslides			N
			/
iv) Other			A N
iv) Onlei			/
			A
5. Environmental Permits	С	X	
This activity is concurrent with final design and must be completed prior to the			
advertisement for construction. Coordinate between the agencies, the			
Environmental Manager and the PM and prepare and submit application and	C	v	
design information to the Environmental Manager for the following permits: 401 Permit Process (Water Quality Certification)	C	X X	<u>i</u>
401 Fermit Process (water Quanty Certification) 402 Permit Process (Point Source Discharge)	C C	X	<u> </u>
404 Permit Process (Discharge of Fill)		X	
i) Determine impacts	C C	X	
ii) CDOT to Coordinate with the U.S. Army Corps of Engineers, Region		21	
and Staff Design (consultant to provide supporting documentation as			
required)	С	X	
iii) Incorporate permit stipulations into the final plans		X	
Senate Bill 40 Certification	С	X	
CDPS or NPDES Storm Water Permit for Construction Activities	С		
6. Structures		X	
Ensure approval of the Foundation Investigation Report from CDOT/PM.	C	X	<u> </u>
7. Hydrology, Hydraulics and Floodplain Management		X	
a. Data Review			
Review data and information developed under the Preliminary Hydraulics			
Report, Preliminary Drainage Report, and/or Preliminary Floodplain Report, and		3.7	
update both/all in accordance with decisions made since the FIR.		X	
b. Hydrology and Hydraulics		X	
i) Review data and information developed under the preliminary hydraulic investigation and update per FIR decisions		X	
ii) Complete final design for minor drainage structures		Λ	
a) Finalize horizontal and vertical locations and sizes for all			
drainage structures based on hydraulic design. Update locations			
in construction plans by highway station or coordinates, as			
appropriate			
b) Make final recommendations for pipe material based on CDOT			
Pipe Material Selection Policy guidelines. Document			
recommendations in a letter with supporting design information.			
c) Finalize structure cross-sections and profiles to determine the			
elevations, flow lines, slopes and lengths of structures. d) Finalize deck/structure drainage in coordination with CDOT Staff			
d) Finalize deck/structure drainage in coordination with CDOT Staff Bridge or their designee.		X	
iii) Complete final design for major structures.		71	<u>i</u>
a) Finalize hydraulic analysis elevations, flow lines, water surface			
profiles and hydraulic information.			
b) Finalize configuration, size and skew of major structures and			
channels.			
c) Coordinate final water surface profiles and final low girder			
elevation for selected structures.			
d) Finalize channel scour profiles for design year and 500-year			
scour for selected structures.			
e) Finalize channel erosion protection limits and mitigation measures for selected structures and provide appropriate details.		X	
measures for selected structures and provide appropriate details.	.i	Λ	i

f) Finalize deck/structure drainage in coordination with CDOT Staff	
Bridge or their designee.	
iv) Complete final design for all drainage details required for minor and	
major drainage structures.	X
v) Recommend culvert pipe sizes, type, shape and material for proposed	
construction detours.	X
vi) Erosion and sedimentation problems identified with solutions in place,	
including but not limited to erosion and scour countermeasure designs,	
analyses and reports.	X
c. Prepare final construction plans in accordance with requirements in the	
CDOT Drainage Design Manual (DDM)	
i) Drainage Notes	
ii) Drainage Tabulation Sheets	
iii) Drainage Plan Sheets	
iv) Drainage Profile Sheets	
v) Drainage Detail Sheets	
vi) Bridge Hydraulic Information Sheets	
vii) Floodplain Information Sheet	X
d. Prepare a Final Hydraulic Design Report or Final Drainage Report in	
accordance with the requirements of the CDOT DDM	X
i) Review data and information in the Preliminary Hydraulic Design	
Report and/or Preliminary Drainage Report and update in accordance	
with decisions made at FIR	
ii) Finalize all sections of the report and include Bridge Hydraulic	
Information Sheets. All design assumptions and related design decisions	
shall be documented in the report.	X
iii) Provide a PDF copy of the Final Hydraulic Design Report or Final	21
Drainage Report to the CDOT Project Manager for disbursement to	
appropriate parties.	X
iv) Floodplain & floodway information incorporated into the plan sheets	X
v) Bridge hydraulic information incorporated into the plan sheet	X
	Λ
vi) Provide digital linework from all drainage and floodplain analysis in	
GIS Shapefiles, AutoCAD/Civil3D drawings, or MicroStation/InRoads	
drawings. All CAD or MicroStation drawings must be compressed into	
a single drawing. All surfaces (DTMs, TINs, Rasters, etc.) must be	
separated and labeled clearly for archiving and rediscovery	X
e. Prepare Final Floodplain Report	X
i) Include the Floodplain Information Sheet from the plan set in 11x17	1.
with all other hydraulic mapping information relevant to requisite	
permits and certifications	X
ii) List and identify all applicable ordinance or code, and describe how	
those specific standards were addressed and <u>resolved</u>	X
iii) Discuss all alternatives analyzed, analysis results, recommendations,	- 11
and final design direction	X
iv) Record all relevant current effective floodplain information, like	21
community number, panel number(s), effective date(s), waterway	
names, cross sections, BFEs, and contact name and information for	
local floodplain administrators contacted for the project.	X
	Λ
v) Provide a copy of approved floodplain development permits and possible no rise certifications	X
	Λ
vi) Identify all construction and as-built stipulations required from	\mathbf{v}
approved permits and certifications	X
vii) Provide all background survey information on 11x17 or smaller	X

	X	
	21	
	X	
	71	
C	v	
C	Λ	
С	X	
	- 11	
С	X	
	21	
C	X	
	21	
С	X	
	- 11	
С	X	
С		
Ŭ	21	
	X	
	·····	
	21	
	X	
	21	
	X	
	21	
: 1		
	Х	
	X	
	X	
	X	
	C C C	C X C X C X

determined	X
iv) Prepare Public Utilities Commission application exhibits as required.	X
10. Subsurface Utility Engineering Create and provide an engineer stamped set of SUE plans that adheres to ASCE 38-22 standards. Create and provide a utility conflict matrix with resolutions to each potential conflict in the work area. Create and provide a test hole log.	X
11. Roadway Design and Roadside Development	X
Roadway design. Prepare and provide final roadway design plans	
incorporating all input from applicable CDOT specialties and outside entities.	X
Roadside design	X
Landscaping	X
i) Determine the most economical alternative, finalize concept, and complete the plan.	X
ii) Verify that an acceptable safe recovery distance exists between traveled way and all trees to be planted.	X
iii) Coordinate special permits that may be required.	X
iv) Verify availability of plant materials and submit letter to the CDOT/PM	A
certifying that designated plants are available.	X
Prepare and provide plans for sprinkler systems, bike paths, sound barriers,	v
truck escape ramps, rest areas, and others, as appropriate.	X
Lighting plans i) Provide a foundation investigation for each high mast light location.	X X
	Λ
ii) After approval of the locations of the lights, the lighting design will be completed with the following information shown on the plan sheets:a) Circuit type and voltage of power source	
b) Location of power source (coordinated with the utility engineer) c) Luminaire type and lumens	
d) Light standard type and mounting height e) Bracket arm type and length	
f) Foundation details	
g) Size and location of electrical conduit	
h) Locations of power sources(s)/lighting control center(s) (if	
appropriate) i) Location of direct burial cable	
1) Location of direct burial cable j) Size of wiring and/or direct burial cable	X
iii) Provide Electrical Line Diagrams for Lighting and Traffic Signals.	Α
iv) Coordinate with local entities	Χ
Prepare and provide wetland mitigation plan.	X
12. Right-of-Way Plans and Activities	
Reference the CDOT ROW and surveying manual' requirements for the following:	X
a. Initiate ROW authorization process	
Coordinate with the CDOT/PM to initiate the ROW authorization process.	
Typically, the corrected FIR plans (with final hydraulic design inputs) will be	
used as the design basis for the ROW authorization plans.	X
b. Ownership Maps	X
c. Authorization Plan:	X
i) Integrate toes of slopes and other design details such as lane lines,	
culverts, road approaches, etc. into ownership map (base map for ROW	
plans)	X
ii) Determine new Right-of-Way requirements, access control, and easements from design plans following the FIR and plot on	
ownership/base maps. Normal scale, 1 inch=50 feet in urban areas,	X

1 inch=100 feet in rural areas. Metric units may be required as per PM.	
Metric scales will be as shown in the CDOT "Metric Conversion	
Manual". Revise numbering of ownerships to correspond to ROW	
acquisitions.	
iii) Calculate areas of parcels, easements, and remainders	X
iv) Prepare ROW plan sheets	X
v) Prepare legal descriptions of parcels, easements and access control	X
vi) Prepare tabulation of properties sheet	X
vii) Prepare Right-of-Way Title Sheet	X
viii) Incorporate the Control Survey and Monumentation Sheets into the	
plans	X
ix) On the Monumentation Sheet, list the ROW, Easement, Control, etc.,	
points to be set and the aliquot corners to be reset	X
x) Prepare ROW tabulation of road approaches, if applicable. Show owner	
milepost/station, right or left of centerline, width of approach, skew	
angle, and any remark	X
xi) Hold ROW Plan Review (ROWPR), with Design, ROW, and	
Construction to determine if ROW plans are sufficient to proceed with	
appraisal of property to be acquired for the project	X
xii) Transmit originals of the plan sheets, title sheet, tabulation of properties	
sheet, and revised ownership (memoranda of ownership and title	
commitments as directed by the ROW manager), calculations and	
supporting data (i.e., parcel diaries), and final electronic data for all	
work products.	X
d. Right-of-Way Plan Revisions	
Revise the ROW plans as needed throughout the appraisal and negotiation	
process for those changes approved by the Region ROW Supervisor. All plan	
revisions shall be submitted to the Region ROW Supervisor within 5	
working days after receiving notice from CDOT to proceed with a Plan	
Revision.	X
e. Final ROW Plans and Monumentation	X
i) ROW Plan Review	X
ii) ROW Plan Revisions, as needed throughout the negotiation and	
appraisal process	X
f. Appraisals	X
g. Appraisal staking	
Stake the proposed ROW line, easements and existing ROW line, if required by	
the region supervisor. Set lath or wooden stakes at all angle points and on line as	
necessary to have at least three stakes visible from any point on line. Mark point	
numbers on all stakes and color code as required. The appraisal stakes only need	
to be set at an accuracy of +/- 1.0 foot, unless the point fall near improvements,	
then +/- 0.25 foot is necessary.	X
h. Title Insurance and Closing Services	
Provide title insurance and closing services as described in the CDOT ROW	
Manual and coordinate with the CDOT Region ROW Manager.	X
i. Acquire needed parcels including title insurance and closing services	
coordinated with the Region ROW Manager	X
13. Final Major Structural Design	
During the conduct of this activity, the Consultant shall participate in structural	
review meetings with the CDOT Structural Reviewer.	X
a. Structure final design	X
i) Perform the structural analysis. Provide superstructure design,	
substructure design and document the design with design notes, detail	X

notes, and computer outputs. Below are the following assumed	
structures: - 88th Avenue Bridge	
- pedestrian path (over or under)	
- retaining walls and/or noise walls	
- overhead sign structures	
- Overhead sign structures	
ii) Perform final design check from design and detail notes.	X
b. Preparation of structure plans and specifications	
Prepare and provide the Structural Plans and Specifications, including any	
revisions identified during the independent check.	X
c. Independent design, detail and quantity check	X
d. Prepare and provide the bridge rating and field packages	X
14. Construction Phasing Plan	
A final construction phasing plan will be developed which integrates the construction	
of all project work elements into a practical and feasible sequence. This plan	
shall accommodate the existing traffic movements during construction, and a	
final traffic control plan will be developed which shall be compatible with the	
phasing plan.	X
15. Preparation for the Final Office Review (FOR)	X
a. Coordinate the packaging of the plans	X
i) Collect plans from all design elements and collate the plan package.	
Include all items listed in the Project Development Manual.	X
ii) Calculate plan quantities and prepare the tabulations and Summary of Approximate Quantities.	X
b. In addition to the plan sheets, the special provisions shall be provided. This	
will consist of those unique Project Special Provisions which have to be written	
specifically for items, details and procedures not adequately covered by CDOT's	
Standard Specifications and Standard Special Provisions. Also a list of the	
Standard Special Provisions which are applicable to the project shall be prepared.	
The Project Special Provisions shall be provided in the CDOT format and	
submitted with the project plans. Appropriate mitigation commitments made	
within any environmental documents should be included in the plans and	
specifications.	X
c. Prepare FOR Estimate.	
Item numbers, descriptions, units and quantities shall be listed and submitted to the CDOT/PM.	X
d. Submit the FOR Plans and specifications (Originals) to the CDOT/PM for a	
preliminary review prior to the FOR.	X
e. FOR plan reproduction not to exceed 5 sets	X
16. Final Office Review	
a. Attend the FOR	X
b. The FOR meeting minutes shall be prepared, approved, and distributed	
within two weeks of the meeting as directed.	X
c. The FOR original plan sheets and the specifications shall be revised in	
accordance with the FOR meeting comments and submitted to the CDOT/PM	***
within four (4) weeks after the FOR.	X
1 0 1 1 1 0 1 1 0 0 0 0 0 0 0 0 0 0 0 0	X
d. Submit the final revision of the plans after CDOT review.	-
E. COMMUNICATIONS (Throughout all of NEPA and Final Design)	
E. COMMUNICATIONS (Throughout all of NEPA and Final Design) 1. Planning (Note: consultant will provide services with review by CDOT R1	
E. COMMUNICATIONS (Throughout all of NEPA and Final Design)	

b. (1) Strategic plan, including schedule and budget (2) updates. Plan includes comms roles/responsibilities, goals, objectives, challenges/issues management, known research, target audiences, key stakeholder list, audience impact map, community engagement plan (including hispanic and EJ outreach), government relations, media relations. social media schedule, tactics, schedule to roll out tactics, measures, budget; and, plan updates if needed		X	
c. (1) Stakeholder list (1) list (monthly) updates. Comprehensive stakeholder list to include all impacted audiences (motorists, residents, businesses, emergency responders, community groups, local/state/federal officials, etc.; monthly checks to update list as needed.		X	
d. Web page content and monthly updates. Develop web page content to include project description, benefits, schedule, maps, engagement (online comment form), links to documents, email and contact information; monthly updates as needed.		X	
e. Customer service (weekly updates). Manage, coordinate timely responses (within three days) and track responses that come through via the website; provide weekly update of calls.		X	
f. Track all outreach. Set up process to track all outreach, meetings, dates of meetings, how many people participated and who presented, update weekly or as needed.		X	
g. Monitor media, including social clips (weekly updates or as needed). Monthly check of media and social media coverage and compile clips to share with the team		X	
h. Set up shared Google drive for shared organization. Work with R1 RCM to set up organizational system of all comms materials and update as needed		X	
2. Internal Meetings			
a. Weekly staff		X	
b. Kickoff meeting and monthly project meetings	С	X	
c. Communications check-in.Touch base meetings with the R1 Communications Manager	С	X	
3. External Outreach		İ	
a. (10) Targeted stakeholder meetings. (10) meetings with smaller groups, HOAs, individuals, council meeting updates, etc. (estimate does not include prep work - that is listed below).		X	
b. (2) Hybrid in-person/virtual meetings. (2) public meetings (estimate does not include the prep work - that is listed below).	С	X	
c. (6) Partner agency meetings. (6) meetings with local agency PIOS and others (estimate does not include prep work - that is listed below).	С	X	
d. *(2) Bus tours. For legislative and community officials - coordinate and schedule tours, prepare presenters, provide materials and take notes.	С	X	
e. *(2) Walking tours. For cycling/multi-modal stakeholders - coordinate and schedule tours, prepare presenter, provide materials and take notes.	С	X	
f. *Online engagement (i.e. Metroquest). Support efforts by reviewing content and questions, PR to attract participants, analyze results for comms needs.		X	
g. *Research. Support efforts by reviewing content and questions, PR to attract participants, analyze results for communications needs.		X	
h. Media relations. Refer calls to CDOT communications, but will help prepare responses if needed.	С	X	
 Content Development (note: materials must be ADA compliant and provided in English and Spanish, consultant to provide services with review by CDOT Communications R1 Manager) 			
a. (1) Project flier and updates as needed. Professionally designed two-sided, 8" x 11" piece (includes project description, benefits, schedule, how people		X	

can engage, map and other graphics, contact info and QR code to wel Easy to download and print, and ADA compliant for web posting.	o page.
b. (3) Rounds of mailed fliers and postcards. First piece to announce the	
project (mail flier) the second two would notify stakeholders of publi	
meetings and info sources.	X
c. (6) E-mail blasts	X
d. (9) E-newsletters	X
(4) = -	X
f (1) FAOs and undated monthly	X
	X
	C X
h. (4) social media posts i. (4) Photography shoots. Shoot images of the (1) site/structures/location	
multi-modal options and the (3 and 4) two public meetings; images n	
convey the area and its diversity and will be used in presentations and	
content.	X
j. (1) Project video (2 mins.)	X
k. (1) Base project PowerPoint presentation (2) public meeting presenta	
(10) individual presentations for smaller meetings.	X
1. (3) Media releases	C X
m. Project business cards	X
n. *(2) Flights of digital and print ad content. Create and place ads prior	
public meetings.	X
5. Public Meetings	
a. Develop plan (2) meetings. Plan to include an approach (open house	or
presentation, who will be involved, how stations will be set up, number	
boards, etc.)	X
b. Design and create boards/visuals (10 boards per meeting)	X
c. Develop presentations	X
d. Research and secure location	X
e. Audio visual	X
f. Coordinate meeting set up and break down	X
g. Provide flyers and other content such as comment forms	X
h. Refreshments	X
i. *(1) Telephone town hall	X
	A
F. PRIOR TO AD	
1. Construction Plan Package	
The bid plan construction contract package shall consist of the revised FOR pl	
will completely describe the work required to build the project including property special provisions and detailed quantities.	
	X
a. Electronic and hard copies of the following:	
i) Roadway a) Horizontal and vertical data	
a) Horizontal and vertical data b) Staking data	
c) Earthwork quantities	
d) Cross sections	X
ii) Major structures	Λ
An independent set of the following shall be submitted to the CD	ОТ
Structural Reviewer for each major structure.	~ 1
a) Structure grades	
b) Structure geometry	X
b. Final engineering package. The consultant shall submit copies, in 3-1	
	X
binders of the following:	
binders of the following: i) All project calculations or worksheets	X

Traffic, hydraulics, lighting, pavement design and economic analysis,		
geology foundation report, etc. All reports will have the latest revisions		
included.		
iii) Copies of variances, design decisions, and variance approvals	X	
iv) Project meeting minutes	X	
v) Utility clearance package		
vi) Utility agreements and information regarding the utility location and		
clearance conditions	X	
vii) Maintain an environmental mitigation tracking tool for all		
environmental document commitments.	X	
viii) Bridge construction packet		
ix) Includes bridge grades, geometry, and quantity calculations or		
worksheets	X	
x) Any other information unique to this project and deemed important to		
the effectiveness of construction.	X	
c. Record plans sets		
Three (3) record plan sets for final design of roadways and structures will be		
produced which shall bear the seal and signature of the responsible		
Consultant Engineer on each sheet. One (1) set shall be retained by the		
Consultant for three (3) years. Two sets shall be submitted to CDOT. The	v	
original plan drawings shall not bear a seal.	X	
2. FEMA CLOMR Submittal		
Prepare a Conditional Letter of Map Revision package and submit to FEMA and the		
local Floodplain Administrator for community concurrence, for any work in the		
floodway that alters the BFE or floodway boundary, or as required by the local	X	
permitting agency's Floodplain Administrator.	Λ	
3. Water Rights Reporting		
If the project includes a detention or water quality pond, water rights reporting is required once the pond is substantially complete. See Section 8, Services After		
Design for additional information.	X	
4. All project permits, approved and in-hand.	X	
G. CORRIDOR MANAGEMENT SUPPORT	37	
1. Design Control	X	
a. Provide the required staff, communication equipment and computer systems	v	
with appropriate software for tracking and monitoring the planning efforts.	X	
b. Conduct periodic corridor progress meetings at an interval acceptable to the	v	
CDOT/PM. The following shall be reviewed:	X	
i) Activities complete since the last meeting	X	
ii) Problems encountered	X	
iii) Late activities	X	
iv) Activities required by the next progress meeting	X	
v) Solutions for unresolved and anticipated problems	X	
vi) Information or items required from other agencies	X	
c. Develop a quality assurance program that ensures correct error-free plans	37	
are produced by the project designers.	X	
d. The consultant shall coordinate the technical aspects of the planning efforts	37	
such as:	X	
i) Ensuring that the separate projects all utilize the same reference and	37	
data base for horizontal and vertical control.	X	
ii) Bearings, coordinates, grades and elevations are identical for common	v	
control lines on separate projects.	X	
iii) Earthwork balance is accomplished where appropriate	X	
2. Information Services	X	

a. Provide a management information system to monitor and report progress.			N
This System will include a computer terminal and/or software for the CDOT/PM			^
that the consultant shall furnish and maintain. This system will:			А
i) Provide access to current project data and status (e.g., progress versus		W	
schedules and cost estimates versus budgeted funds)		X	
ii) Include the project schedules for submittals and key events		X	
iii) Identify progress with respect to the schedules		X	
iv) Identify critical path activities		X	
v) Provide upon demand the scheduled submittals/key events for			
designated time periods		X	
b. Produce and periodically update a strip map which outlines the entire			
corridor. The Information Shown on this Map will Include the following:		X	
i) Preliminary engineering project limits		X	
ii) Construction project limits		X	
iii) Construction project estimated costs		X	
iv) Construction project Advertise-for-Bid (AD) dates		X	
v) Other information that is considered appropriate		X	
3. Budget Planning Support			
a. Maintain a current file of project cost estimates. The date and type of each			
estimate will be identified.		X	
b. Maintain a current file of existing and proposed funding for projects. Types			
of funding sources will be identified.	С	X	
c. Develop a proposed ad schedule based on the estimated costs and the			
existing and anticipated future funding. The proposed ad schedule will be			
compared to the design schedule. Adjustments to the design and ad schedules			
may be made with CDOT concurrence.	С	X	
d. A continuing evaluation of cash flow requirements and drawdown schedules			
administrative, preliminary engineering, right-of-way, utility, and construction			
costs will be accomplished. The funding requirements will be compared with the			
budget, also on a continuing basis. CDOT will be notified immediately of			
changes in funding requirements. (this will be completed when needed)		X	

SECTION 8 SERVICES AFTER DESIGN

Note: The Consultant shall appoint a responsible member of the firm to be the contact person for all construction services. That person should be available until the end of construction to coordinate the following services.

Deliverables can be static reports and products, digital reports and products, and/or GIS data layers. The scope should be specific as to what type of deliverable is expected.

This list establishes the individual task responsibility. Those tasks identified as CDOT/Other should utilize an abbreviation system to indicate whether the task will be completed by CDOT or another agency (i.e. "C" for CDOT and abbreviations as provided below). The consultant shall maintain the ability to perform all work tasks which are indicated below by an 'X' in the consultant column, in accordance with the forms and conditions contained herein, and the applicable CDOT standards. Where appropriate, mark "N/A" for not applicable items.

*Other Agency Abbreviations:

A. Other

	C D O T (C) / O t h e r *	C on su lta nt	N ot A pp lic ab le
A. REVIEW OF SHOP DRAWINGS			
Review contractor shop and auxiliary drawings as directed by the CDOT/PM.		X	
1. Maintain a log of all submittals which includes the following information:		X	
a. Submittal description		X	
b. Date received		X	
c. Date transmitted back to the sender		X	
The review of submittals shall be done by a licensed professional engineer who is acceptable to the CDOT/PM.		X	
3. Review Shop Drawings Review the construction contractor's shop drawings for conformance and compliance with the contract documents, the provisions of the current "Standard Specifications for Road and Bridge Construction, and the period of work shown in the CDOT specifications in conjunction with the contract work.	С	X	
B. CONSTRUCTION SERVICES			
When requested by the appropriate Program Manager, the Consultant shall provide the services described below			N/ A
Coordinate Schedule Coordinate and evaluate contractor's construction schedule at start of construction and continuously throughout construction phase.			N/ A

	C D O T (C) / O t h e r *	C on su lta nt	N ot A pp lic ab le
2. Provide field observation prior to, and on the day of, the following:			N/ A
a. Pile driving and/or caisson drilling			İ
b. All major concrete pours			
c. Placement of girders			
d. Splicing of girders			
e. Post-tensioning duct and anchorage placement			
f. Post-tensioning operations			
3. Technical Assistance			
Provide technical assistance to CDOT project personnel on an as-needed basis. This			
service shall include, but not be limited to, the following:		X	
a. Respond to questions in the field that arise relative to the plans, details			
or special provisions		X	
b. Review girder erection plan		X	
4. Report Submittal			
The following reports/submittals shall be maintained and submitted:			
a. Diary - A complete diary will be accomplished daily for each field			N/
observation activity.			A
b. Documentation/justification - Changes/revisions/documentation			
justifying changes and/or revisions to plans and specifications		X	
c. Progress reports - Monthly progress reports will be submitted for the			N/
Consultant's activities.			A
d. Calculations, drawings, and specifications as needed.		X	
e. Daily time sheets - This will be filled out daily on a form approved by			N/
the Project Engineer. This sheet will remain with the Project Engineer.			A
5. Project Initiation and Meetings		X	
6. Field Coordinations		X	
7. Review RFI's		X	
8. Plan Revisions		X	
C. POST DESIGN PLAN MODIFICATIONS			
 When requested by the Program Manager through the CDOT/PM, the Consultan shall provide design services for plan modifications required by unforeseen field conditions. 			
Revisions to PWQ CMs and drainage design should be performed by the Engineer of Record.		X	

	C D O T (C) / O t h e r *	C on su Ita nt	N ot A pp lic ab le
1. Final Earthwork or Interim Determination			3.7/
Compute the final or interim as-built earthwork quantities. This will include the required			N/
surveying, engineering technician, and computer support.			Α
2. "As-Built" Plans			3.7/
Redline the original plan set in a "track changes" manner so that design information is			N/
shown alongside as-constructed information.			А
3. PWQ CM GIS Attribute Tables and Feature Classes Information shall be submitted that mosts all the properties requirements of the MSA.			
Information shall be submitted that meets all the reporting requirements of the MS4			
Permit and the CDOT PWQ Program, including pond volume certification. Finalize draft Operations & Maintenance plan for each PWQ CM using project as-builts.		X	
4. Revisions to the Final Right-of-Way Plans		Λ	<u> </u>
Review the final Right-of-Way line to identify any excess property due to construction changes. Prepare Final Plan Revisions, including legal Descriptions of excess property		X	
5. Monument the Right-of-Way			
Reset all monuments referenced prior to construction that have been damaged or destroyed.			N/ A
b. Reset any control monuments disturbed or destroyed by construction that are necessary to set Right-of-Way monuments.			N/ A
c. Set all new Right-of-Way monuments as shown on final plans (or			N/
reference monuments, if necessary).			A
6. Set property corners on all remainder parcels			N/
Required monumentation will be as directed by the CDOT/PM.			A
7. Deposit ROW Plans			
A Record Plan Set updated for revisions and showing all monuments set subsequent to			
construction, must be signed and sealed by the Professional Land Surveyor			
responsible for the work. The Record Set must be deposited in the appropriate county			
office in accordance with CRS 38-50-101 and CRS 38-51-107. A copy of the			N/
deposited plan set must be delivered to the CDOT/PM.			A
8. FEMA LOMR Submittal			
Prepare a Letter of Map Revision package and submit to FEMA after receiving approval from the community Floodplain Administrator. This LOMR shall be based on the P.L.S. certified as-built topographic information and corresponding modifications to the modeling and report that were submitted to FEMA for the CLOMR application			
for all work that will alter the regulatory floodplain or floodway, or as required by the		37	
local permitting agency's Floodplain Administrator.		X	1

	C D O T (C) / O t h e r *	C on su lta nt	N ot A pp lic ab
9. Update Floodway No Rise Certification Stipulations for no rise in regulatory floodways often include as-built surveys, certifications, and other operational standards. Check project specials from CDOT and floodplain development permit stipulations from local agencies issuing the permit to determine what is required.		X	
10. Water Rights Reporting Submit pond information to the water rights reporting website. Pond information submitted should reflect the as-built condition for pond volume and stage/storage/discharge relationships, and any other information requested by the water rights reporting website during upload.		X	

SECTION 9 CONTRACT CONCLUSION (CHECKLIST)

1. SUPPLEMENTAL WORK

It is anticipated that this contract may be supplemented for:

- A. Preliminary Design
- B. Final Design
- C. Construction Services
- D. Construction Engineering
- E. Final Earthwork Determination
- F. Completion of the "as-built" plans, PWQ Operation and Maintenance Plan sheet and/or final ROW plans

2. CONTRACT COMPLETION

This Contract will be satisfied upon acceptance of the following items if applicable:

- A. Project Schedule
- B. Project Progress Meeting Minutes
- C. Traffic Control Plan(s)
- D. All documents found In Research
- F. All Permission to Enter Property forms
- G. Monumented & Surveyed Ground Control Diagram(s)
- H. Legally Deposited Control Survey Diagram(s)
- I. Digital TMOSS Data
- J. Photography Products
- K. Ownership Map
- L. Survey Report (including monument recovery forms)
- M. Monumented and Sealed ROW Plans
- N. Legally Deposited Survey Plans
- O. Legal Descriptions (Signed and Sealed)
- P. NOAA-NGS Blue Book
- Q. Completion of review of contract submittals
- R. Design Plans, Specifications, and Final Estimate
- S. All Environmental Permits
- T. All Environmental, Utility, and ROW Clearances
- U. Floodplain Report
- V. Hydraulic Design Report, including PWQ design (signed and sealed)
- W. Structural Report (signed and sealed)
- X. Geotechnical Report (signed and sealed)
- Y. Materials Report
- Z. Environmental Technical Resource Reports
- AA. Environmental NEPA Documents
- AB. Floodplain Development Permit & No Rise Documents
- AC. GIS shape files
- AD. PWQ Operation & Maintenance plan for each PWQ CM

TABLE 1 – SUBMITTALS

Note: This list establishes the individual task responsibility. Those tasks identified as CDOT/Other should utilize an abbreviation system to indicate whether the task will be completed by CDOT or another agency (i.e. "C" for CDOT and abbreviations as provided below). The consultant shall maintain the ability to perform all work tasks which are indicated below by an 'X' in the consultant column, in accordance with the forms and conditions contained herein, and the applicable CDOT standards. Where appropriate, mark "N/A" for not applicable items.

*Other Agency Abbreviations:

Hard Copy		tronic opy	Work Tasks	C D O T (C)/ O th er	C o ns ul ta nt	N ot A pp lic ab le
	PD F	Ori g.				
X		X	Periodic Reports			
X	X		Billings	C	X	
X		X	Meeting Minutes		X	
X	X		Project Schedule		X	
X		X	Completed Specific Design Criteria		X	
X	X		Survey Plan		X	
X	X		Approved MHT's		X X	
X	X		Traffic Control Supervisor Certification		X	
X	X		Permissions to Enter		X	
		X	Initial Submittal of TMOSS (?) and or MOSS Compatible Data		X	
X	X	X	Initial Submittal of an Original Plan Sheet		X	
			Project Development			
X		X	Public Communication Contact List		X	
			Route Location Survey			
X	X		Traffic Control Supervisor Certification			
X	X		Approved MHT's			
		X	Survey data in raw, unedited formats		X	
X		X	Pothole data including invert elevations		X	
X	X		Existing culverts report		X	<u> </u>
X	X		Access report		X	
X	X		Topographic survey notes		X	
X	X	X	Contour plan checked for errors		X	
X	X	X	Survey control diagram		X	
X			Field books		X	<u> </u>
		X	Electronic Survey Files		X	
		X	Survey TMOSS Data		X	<u> </u>
X		X	Monument Records		X	

Hard Copy	Electronic Copy	:		Work Tasks	C D O T (C)/ O th er	C o ns ul ta nt	N ot A pp lic ab le
	PD F	Ori g.					
X	X	ь. Х	Control & Monumentation Plan Sheets		X	<u> </u>	
X	X		Aerial Photography Index Map Sheets				
X	X		Aerial Photography Contact Sheets		<u>.</u>		
			Permits				
X	X		401 Permit		X		
X	X		Dewatering / 402 Permit		X		
X	X		404 Permit		X		
X	X		SB 40 Permit		X		
X	X		Wildlife Certification		X		
X	X		CDPS Storm Water Permit	С			
X	X		CDPHE Discharge Permit		X		
	X		Floodplain Development Permit (approved)		X		
	X		No Rise Certification (approved)	-	X	<u> </u>	
	X		No Rise Recertification at As-Built (approved)	-	X	<u> </u>	
	21		Environmental Work Tasks	<u> </u>	- 21	<u>-</u>	
X	X	X	Appropriate NEPA Document (CatEx, EA, EIS, FONSI or ROD)		X		
X	X	X	Figures and Exhibits from NEPA Document	<u> </u>	X	<u>-</u>	
X	X	X	Air Quality Technical Report		X		
X	X	X	Geologic Technical Report		X		
X	X	X	Water Quality Technical Report		X		
X	X	X	Wetland Finding Report	-	X	<u> </u>	
X	X	X	Integrated Noxious Weed Management Plan	<u> </u>	X	<u>-</u>	
X	X	X	Biological Resources Report	<u> </u>	X	<u>-</u>	
X	X	X	Biological Assessment	<u> </u>	X		
X	X	X	Historic Resource Technical Reports		X		
X	X	X	Section 4(f) Documents	<u> </u>	X		
X	X	X	Paleontological Technical Report	<u>.</u>	X	<u> </u>	
X	X	X	Environmental Justice Technical Report	<u> </u>	X	<u> </u>	
X	X	X	Transportation Technical Report	<u> </u>	X	<u> </u>	
X	X	X	Noise Technical Report		X		
X	X	X	Hazardous Materials Documentation (ISA/MESA)		X		
			PRELIMINARY DESIGN	<u> </u>	<u> </u>		
		X	Electronic Survey Data	<u>.</u>	X	<u> </u>	
X	X	∠ \	Traffic Data & Recommendations	<u>.</u>	X	<u> </u>	
71	X		Geology & Soils Investigation Report		X		
X	X		Pavement Design Report		X		
Х Х	X		Existing Bridge Condition Report		X		
/ 1	X	<u>:</u>	Foundation Investigation Report	<u>.</u>	X	<u>:</u>	

Hard Copy	Electronic Copy		Work Tasks	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A pp lic ab le
	PD F	Ori g.				
X	X		Engineering Geology Plan Sheet(s)		X	<u> </u>
X	X		Preliminary Hydraulic Design Report, including preliminary PWQ design		X	
	X		Preliminary Floodplain Report		X	<u> </u>
X	X	X	Preliminary Storm Water Management Plan		X	<u> </u>
X	X		Utility Relocation Recommendations		X	ļ
X	X	X	Irrigation Ditch Structure Plans		X	<u> </u>
			Right-of-way			<u> </u>
X	X		Memorandum of Ownership		X	<u> </u>
X	X	X	Preliminary Ownership Map (include in FIR Plan set)		X	
X	X		Structural Selection Report	<u> </u>	X	<u> </u>
X	X		Foundation Investigation Request		X	<u> </u>
X	X		Final Materials Recommendations		X	<u> </u>
X	X		Final Pavement Selection Report		X	
X	X		Intersection Traffic Report		X	
X	X		Traffic Report		X	
X	X		Preliminary Cost Estimate	<u>. [</u>	X	<u> </u>
X	X	X	FIR Plan Set		X	<u> </u>
X	X		List of deviations from Standard Design Criteria		X	<u> </u>
X	X	X	Corrected FIR Plan Set		X	
			FINAL DESIGN			
X	X	X	ROW Authorization Plans		X	<u> </u>
	X		Final Hydraulic Design Report, including PWQ design		X	
	X		Final Floodplain Report		X	ļ
X	X	X	Final Utility Plan Set		X	<u> </u>
X	X	X	Final SUE Stamped Plan Set	<u> </u>	X	<u> </u>
X	X	X	Final Railroad Plan Set		X	<u> </u>
X	X		PUC Exhibit		X	ļ
X			Bound Final Geotechnical Report copies		X	<u> </u>
X	X		Correspondence with Agencies, Entities, and Public		X	
			Right-of-way			ļ
X	X		Area Calculations		X	<u> </u>
X	X	X	Authorization Plans	<u> </u>	X	<u> </u>
X	X		Legal Descriptions		X	<u> </u>
X	X	X	Final Right-of-way Ownership Map		X	<u> </u>
X	X	X	Stabilization Plans	:	X	1

Hard Copy	Electronic Copy		Work Tasks	C D O T (C)/ O th er	C o ns ul ta nt	N ot A pp lic ab
	PD	Ori				
	F	g.				
X	X		Safety Assessment		X	
X	X	X	Signing/Pavement Marking Plans		X	<u> </u>
X	X		Signal Warrant Study		X	
X	X	X	Signalized Intersection Plans & Specifications		X	
X	X	X	Traffic Control Plan		X	
			Roadside Planning		<u></u>	
X	X	X	Landscape Plan & Specifications		X	<u> </u>
X	X		Certification of Plant Availability		X	
X	X	X	Irrigation Plans & Specifications		X	
X	X	X	Bike path Plans & Specifications		X	
X	X	X	Sound Barrier Plans & Specifications		X	
X	X	X	Truck Escape Ramp Plans & Specifications	<u></u>	X	
X	X	X	Rest Area Plans & Specifications	<u></u>	X	
X	X	X	Lighting Plans & Specifications	<u></u>	X	
X	X	X	Structure Final Review Plans & Specifications		X	
X	X	X	Construction Phasing Plan		X	
X	X	X	Storm Water Management Plan & Specifications		X	
X	X		FOR Plans & Specifications		X	
X	X		FOR Cost Estimate		X	
X	X	X	Final Review Revisions	:	X	
			Construction Plan Package	:		
37	37	37	Final Plans (11X17), Specifications (duplex) &		37	
X	X	X	Estimate Package for Ad.		X	
X	X	X	Final Cross Sections		X	
X	X		Schedule of Quantities		X	
X	X		Design Decisions		X	
X	X		Variances		X	
X	X		Findings In the Public Interest		X	
		X	Original Surface Digital Terrain		X	
		X	Final Surface Digital Terrain Model		X	
		X	Design Digital Terrain Model		X	
X		X	Staking Data		X	
X	X	X	Earthwork Quantities		X	
X	X	X	Mass/Haul diagram		X	
X	X		Project Calculations (2 copies)		X	
X	X		Worksheets (2 copies)		X	
X	X		Design Notes		X	
X	X		Independent Design Review Reports		X	
X	X		Roadway Design Data Submittal		X	
X	X	<u> </u>	Major Structure Design Final Submittal	<u>.</u>	X	<u> </u>

Hard Copy	Electronic Copy		Work Tasks	C D O T (C)/ O th er *	C o ns ul ta nt	N ot A pp lic ab le
	PD F	Ori g.				
X	X	a-	Bridge Construction Pack		X	
X			Record Plan Sets		X	
X	X		As-Built Plan Sets (if required)		X	
X	X		Approved no rise recertification or written and approved evidence that all floodplain permit conditions are resolved		X	

APPENDIX A REFERENCES

1. <u>AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION</u> <u>OFFICIALS (AASHTO) PUBLICATIONS</u> (using latest approved versions):

- A. A Policy on Design Standards-Interstate System
- B. A Policy on Geometric Design of Highways and Streets
- C. Guide for Design of Pavement Structures
- D. LRFD Bridge Design Specifications
- E. Guide for the Design of High Occupancy Vehicle and Public Transfer Facilities
- F. Guide for the Development of Bicycle Facilities
- G. Standard Specifications for Transportation Materials and Methods of Sampling and Testing Part 1, Specifications and Part II, Tests
- H. Highway Design and Operational Practices Related to Highway Safety
- I. Roadside Design Guide
- J. Load Resistance Factor Design (LRFD) Specifications

2. COLORADO DEPARTMENT OF TRANSPORTATION PUBLICATIONS (using latest approved versions):

- A. Design Guide (all volumes)
- B. Bridge Design Manual
- C. Bridge Detailing Manual
- D. Bridge Rating Manual
- E. Geotechnical Design Manual
- F. Project Development Manual
- G. Erosion Control and Stormwater Quality Guide
- H. Field Log of Structures
- I. Cost Data Book
- J. CDOT Traffic Analysis and Forecasting Guidelines
- K. Drainage Design Manual
- L. Landscape Architecture Manual
- M. NEPA Manual
- N. Environmental Stewardship Guide
- O. Interim Guidance GHG Guidance for CDOT to meet Part 4 of CRS 43-1-128.
- P. Various CDOT Environmental Resource Guidance (i.e Air Quality, Hazardous Materials, Noise, Visual)
- Q. Quality Manual
- R. Survey Manual

- S. Field Materials Manual
- T. Standard Plans, M & S Standards
- U. Standard Specifications for Road and Bridge Construction and Supplemental Specifications
- V. Item Description and Abbreviations (with code number) compiled by Engineering Estimates and Market Analysis Unit ("Item Book")
- W. Right-of-Way Manual
- X. The State Highway Access Code
- Y. Utility Manual

Q. No. 1905.1

Branch

- Z. TMOSS Generic Format
- AA. Field TMOSS Topography Coding
- BB. Topography Modeling Survey System User Manual
- CC. Interactive Graphics System Symbol Table
- DD. M-E Pavement Design Manual

3. <u>CDOT PROCEDURAL DIRECTIVES</u> (using latest approved versions):

A.	No. 27.1	Social Marketing – Use of Web 2.0 and Similar Applications				
B.	No. 31.1	Web Site Development				
C.	No. 400.2	No. 400.2 Monitoring Consultant Contracts				
D.	No. 501.1	Requirements for Storm Drainage Facilities and Municipal Separate Storm				
	Sewer System Facilities					
E.	No. 503.1	Landscaping with CO Native Plant Species and Managing the CO Pollinator				
	Highway					
F.	No. 514.1	Field Inspection Review (FIR)				
G.	No. 516.1	Final Office Review (FOR)				
Н.	No. 1050.1	Contracts with Local Agencies for Maintenance of State Highways				
I.	No. 1217a	Survey Request				
J.	No. 1304.1	Right-of-Way Plan Revisions				
K.	No. 1305.1	Land Surveys				
L.	No. 1601	Interchange Approval Process				
M.	No. 1700.1	Certification Acceptance (CA) Procedures for Location and Design Approval				
N.	No. 1700.3	Plans, Specifications and Estimates (PS&E) and Authorization to Advertise for				
	Bids under Certifications Acceptance (CA)					
O.	No. 1700.5	Local Entity/State Contracts and Local Entity/Consultant Contracts and Local				
	Entity/R.R. Contracts under C.A					
P.	No. 1700.6	Railroad/Highway Contracts (Under Certification Acceptance)				

Preparation of Plans and Specifications for Structures prepared by Staff Bridge

4. FEDERAL PUBLICATIONS (using latest approved versions):

- A. Manual on Uniform Traffic Control Devices
- B. Highway Capacity Manual
- C. Urban Transportation Operations Training Design of Urban Streets, Student Workbook
- D. Reference Guide Outline Specifications for Aerial Surveys and Mapping by Photogrammetric Methods for Highways
- E. Executive Order 12898
- F. Executive Order 11988 & 13690 FHWA Federal-Aid Policy Guide
- G. FHWA NHI Hydraulic Circular (HEC) and Hydraulic Design Series (HDS) Reports
- H. Technical Advisory T6640.8A
- I. U.S. Department of Transportation Order 5610.1E
- J. Geometric Geodetic Accuracy Standards and Specifications for Using GPS Relative Positioning Techniques
- K. ADAAG Americans With Disabilities Act Accessibility Guidelines
- L. 23 CFR 771, the FHWA Technical Advisory T6640.8A
- M. 44 CFR 59-72, standards of the National Flood Insurance Program (NFIP)
- N. U.S. Army Corps of Engineers Wetlands Delineation Manual of 1987 and appropriate regional supplements

5. AREA:

- A. Manual for Railway Engineering
- B. Urban Storm Drainage Criteria Manual (MHFD, formerly UDFCD)
- C. Any appropriate local agencies references as appropriate

APPENDIX B SPECIFIC DESIGN CRITERIA

Note: The following criteria will be developed by the consultant and coordinated with the CDOT/PM prior to starting the design. The Consultant shall develop the CDOT Form 463 and insert a copy upon completion.

1. ROADWAY

A. BASIC DESIGN

The basis for design will be the data in CDOT Form 463, Design Data. A copy of the latest applicable Design Data form will be furnished to the consultant.

B. GEOMETRIC AND STRUCTURE STANDARDS:

- a Design Speed, horizontal alignment, curvature, vertical alignment, sight distance and superelevation is specified in Form 463.
- b Use of Spirals [Yes/No]
- c Passing Sight Distance
- d Decision Sight Distance
- e Frontage Roads, Separation Width
- f CDOT Access Code
- g Airway Highway Clearances Design Guide
- h Bridges and Grade Separation Structures, Clearances to Structures and Obstructions, CDOT Design Guide
- i Curb and Gutters, Type
- C. GEOMETRIC CROSS SECTION are as specified in Form 463
- D. INTERSECTIONS AT GRADE:
 - a. Type
 - b. Special Considerations

E. TRAFFIC INTERCHANGES:

- a. Type
- b. Ramp Type
- c. Special Considerations

F. DESIGN OF PAVEMENT STRUCTURE:

- a. Pavement Type & Percent Trucks are as specified in Form 463
- b. Economic Analysis Period
- c. Design Life

G. MISCELLANEOUS DESIGN CONSIDERATIONS:

- a. Fence Type
- b. FEMA Flood Zone
- c. Design Flood Frequency

H. ROADSIDE DEVELOPMENT

- a. Landscaping
- b. Specifications for Revegetating Disturbed Areas to be provided by CDOT
- c. PWQ Design
- d. Noise Control
- e. Type
- f. Guardrail and End Treatments

I. LIGHTING:

a. Type

APPENDIX C DEFINITIONS

Note: For other definitions and terms, refer to Section 101 of the CDOT Standard Specifications for Road and Bridge Construction and the CDOT Design Guide.

AASHTO American Association of State Highway & Transportation Officials

ADT Average two-way 24-hour Traffic in Number of Vehicles

AREA American Railway Engineering Association
ATSSA American Traffic Safety Services Association
AT&SF Atchison, Topeka & Santa Fe Railway Company

ADAAG Americans with Disabilities Accessibility Act Guidelines

BAMS Bid Analysis and Management Systems

BFE Base Flood Elevation

BLM Bureau of Land Management
BNRR Burlington Northern Railroad

CA Contract Administrator – The CDOT Manager responsible for the satisfactory completion of the

contract by the consultant

CAP CDOT's Action Plan
CBC Concrete Box Culvert

CDOT Colorado Department of Transportation

CDOT/PM Colorado Department of Transportation Project Manager – The CDOT Engineer responsible for

the day to day direction and CDOT Consultant coordination of the design effort (as defined in

Section 2 of this document)

CDOT/STR Colorado Department of Transportation Structure Reviewer – The CDOT Engineer responsible for

reviewing and coordinating major structural design

CDPHE Colorado Department of Public Health and Environment

CEQ Council on Environmental Quality

COG Council of Governments
COGO Coordinate Geometry Output
CONSULTANT Consultant for the project

CONTRACT Typically, a Region Engineer or Branch Head. The CDOT employee directly responsible for the ADMINISTRA satisfactory completion of the contract by the Consultant. The contract administration is usually

TOR delegated to a CDOT Project Manager (as defined in Section 2 of this document).

C/PM Consultant Project Manager – The Consultant Engineer responsible for combining the various

inputs in the process of completing the project plans and managing the Consultant design effort.

CWCB Colorado Water Conservation Board

DDM Drainage Design Manual

DEIS Draft Environmental Impact Statement

DHV Future Design Hourly Volume (two-way unless specified otherwise)

DRCOG Denver Regional Council of Governments

D&RGW Denver & Rio Grande Western Railroad

EA Environmental Assessment
EIS Environmental Impact Statement
ESAL Equivalent Single Axle Load

ESE Economic, Social and Environmental

FEIS Final Environmental Impact Statement
FEMA Federal Emergency Management Agency
FHPG Federal Aid Highway Policy Guide
FHWA Federal Highway Administration

FIPI Finding In Public Interest FIR Field Inspection Review

FONSI Finding of No Significant Impact

FOR Final Office Review

GIS Geographic Information Systems
GPS Global Positioning System

LA Professional Landscape Architect registered in Colorado

MAJOR Bridges and culverts with a total clear span length greater than twenty feet. This length is measured structures along the centerline of roadway for bridges and culverts, from abutment face to abutment face.

Retaining structures are measured along the horizontal distance along the top of the wall. Structures

Retaining structures are measured along the horizontal distance along the top of the wall. Structures with exposed heights at any section over five feet and total lengths greater than a hundred feet as well as overhead structures including (bridge signs, cantilevers and butterflies extending over

traffic) are also considered major structures.

MHFD Mile High Flood District (formerly UDFCD)

MPO Metropolitan Planning Organization (i.e. Denver Regional Council of Governments, Pikes Peak

Area Council of Governments, Grand Junction MPO, Pueblo MPO, and North Front Range

Council of Governments).

MS4 Municipal Separate Storm Sewer System
NEPA National Environmental Policy Act
NFIP National Flood Insurance Program

NGS National Geodetic Survey

NICET National Institute for Certification in Technology NOAA National Oceanic and Atmospheric Administration

PAPER SIZES See Computer-Aided Drafting Manual (CDOT); Table 6-13 and Table 8-1

PE Professional Engineer registered in Colorado

PM Program Manager

PLS Professional Land Surveyor registered in Colorado

PRT Project Review Team

PS&E Plans, Specifications and Estimate PROJECT The work defined by this scope

PWQ CM Permanent Water Quality Control Measure

ROR Region Office Review

ROW Right-of-Way: A general term denoting land, property, or interest therein, usually in a strip

acquired for or devoted to a highway

ROWPR Right-of-Way Plan Review
RTD Regional Transportation Director
T/E Threatened and/or Endangered Species

SFHA Special Flood Hazard Area
SH State Highway Numbers

TMOSS Terrain Modeling Survey System

TOPOGRAPHY In the context of CDOT plans, topography normally refers to existing cultural or manmade

details.

USACE United States Army Corp of Engineers