

TO ESTABLISH GEOMETRIC CONTROL FOR THE CONSTRUCTION OF THIS PROJECT, THE DEPARTMENT HAS PROVIDED THE FOLLOWING INFORMATION:

Format *
 3D Design Modeling Electronic Files _____
 Horizontal Control _____
 Vertical Control _____
 Roadway Alignment _____
 Original Terrain Data _____
 Other: _____

* Specify the information format, ie., plan sheet, computer disk, computer printout, or other. The information marked is either contained on the plans or is available from the Engineer.

TYPE OF PROJECT

Landscaping
 Signalization
 Safety Improvement
 Asphalt Overlay
 Concrete Overlay
 Minor Widening
 Major Reconstruction
 New Roadway Construction
 Bridge Replacement
 Bridge Widening
 New Bridge
 Other: _____

SURVEY WORK TO BE PERFORMED BY OTHERS: _____

WORK PERFORMED BY THE CONTRACTOR'S SURVEYOR UNDER SECTION 625:

- A complete passing Base Line report (completed within 6 months prior to the start of the project)
- An instrument calibration Certification (completed within 6 months prior to the start of the project)
- Establish and Maintain Project Centerline or Engineer Approved Offset Line(s)
- Verification and Maintenance of Horizontal and Vertical Control
- Verify or Determine existing grades and alignments
- Verify or Determine existing topography
- Clearing and Grubbing Limits (Section 201)
- Removal Limits (Section 202)
- Reset Items (Section 210)
- Excavation and Embankment (Section 203)

- Excavation
 Unclassified
 Stripping
 Muck
 Rock
 Borrow
 Other: _____
 Potholing

- Embankment
 Site Grading
 Erosion Control (Perm)
 Other: _____
 As Staked Earthwork Quantities (See General Notes)

- Landscaping
 Top Soil (Section 207)
 Seeding (Section 212)
 Mulching (Section 213)
 Planting (Section 214)
 Herbicide (Section 217)
 Other: _____

- Erosion Control (Section 208)
 Seeding (Temp)
 Silt Fence
 Erosion Bales
 Erosion Logs
 Riprap (Temp)
 Other: _____

- Roadway Bases
 Untreated Subgrade
 Treated Subgrade
 Aggregate Base Course (Section 304)
 Reconditioning
 PMBB - Plant Mix Bituminous Base
 Other: _____

	Slope Staking (Y/N)	Grid (Y/N)	Grade (Y/N)	Special Interval
Excavation	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-

	Slope Staking (Y/N)	Grid (Y/N)	Grade (Y/N)	Special Interval
Embankment	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-

	Grid (Y/N)	Grade (Y/N)	Special Interval	Special Offset
Roadway Bases	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-

- Pavements
 HMA - Hot Mix Asphalt (Section 403)
 Concrete (Section 412)
 Heating & Scarifying Treatment
 Prime Coat, Tack Coat & Rejuvenating Agent (Section 407)
 Seal Coat or Chip Seal (Section 409)
 Other: _____

	Grid (Y/N)	Special Interval	Special Offset
Pavements	-	-	-
	-	-	-
	-	-	-
	-	-	-
	-	-	-

- Roadway Elements
 Curb and Gutter (Section 609)
 Drop inlets - alignment and grades (Section 604)
 Retaining Walls
 Guard Rail (Section 606)
 Sidewalk (Section 608)
 Overlay Stationing
 Other: _____

	Tangent Interval	Curve Interval	Special Offset
Curb & Gutter	-	-	-
	-	-	-
	-	-	-
	-	-	-
	-	-	-

- Riprap (Perm) (Section 506)
 Slope and Ditch Paving (Section 507)

	Left Interval	Center Interval	Right Interval
Stationing	-	-	-
	-	-	-
	-	-	-
	-	-	-
	-	-	-

- Minor Structures
 Structure Excavation limits (Section 206)
 Culverts (Section 603)
 Culverts w/ Headwalls and Wingwalls (Section 601)
 Concrete Box Culverts w/ Headwalls and Wingwalls
 Pipes (Section 603)
 Sanitary Sewer
 Storm Sewer
 Water
 Irrigation
 Miscellaneous
 Manholes (Section 604)
 Inlets (Section 604)
 Permanent Water Quality BMP (Section 208)
 Other: _____

- Major Structures - Overhead Signs (Section 614), Concrete Box Culverts, Bridges - and all other structures assigned a structure number
 Structure Excavation limits (Section 206)
 Concrete Box Culverts (Section 603) w/ Headwalls and Wingwalls (Section 601)
 Piling locations and cut off elevations (Section 502)
 Caisson locations and elevations (Section 503)
 Footing locations, alignment, and elevations
 Abutment/Pier locations, alignment, and elevations
 Wingwall skew angles/offsets
 Structural concrete form locations
 Substructure As-constructed survey required for Bridges (Subsection 601 .12) and Overhead signs (S-614-50)
 Bridge expansion joint(s) alignment and grade (longitudinal and transverse)
 Deck grades at Girder 10th or "n" th point locations and elevations
 Slope and Ditch Paving (Section 507)
 Other: _____

- Fencing (Section 607)
 Temporary
 Permanent
 Sound Barrier
 Other: _____

- Delineators (Section 612)
 Temporary
 Permanent

- Lighting (Section 613) and Traffic Control Devices (Permanent) (Section 614)
 Signal pole locations and elevations
 Light pole locations and elevations
 Sign locations
 Field verify sign post locations, elevations, and lengths before fabrication.
 Other: _____

- Pavement Marking (Section 627)
 Striping (Temp)
 Striping (Perm)
 Symbols
 Other: _____
 Temporary Lighting and Construction Traffic Control Devices (Section 630)
 Signal pole locations and elevations (Temp)
 Light pole locations and elevations (Temp)
 Sign Locations (Temp)
 Other: _____
 All Easements (Temp Staking by P.L.S. Only)
 Right of Way (Temp Staking by P.L.S. Only)

WORK PERFORMED BY THE CONTRACTOR'S SURVEYOR UNDER SECTION 629:

- Monumentation (Section 629)
 Control
 Right of Way
 Land corners, Aliquot corners
 Easements
 Reference the specified existing monuments: ** _____
 Replace the specified existing monuments: ** _____
 Locate monuments. It is estimated _____ hours are required.

NOTE: All 629 items shall include adequate research, calculations, and evaluations of evidence for monuments to be set.

** A Tabulation of Survey Monuments may be provided on the plans.

GENERAL NOTES:

- Unless indicated otherwise on this Survey Tabulation Sheet, all survey work and staking intervals shall be done in accordance with the latest edition of the CDDT Survey Manual.
- Adequate information for establishing lines, grades, and locations for all work items have been specified on the plans. Any additional information required to stake the item or element shall be generated by the Contractor's surveyor.
- The Contractor's surveyor shall provide an estimate of the man-hours necessary to complete the work items indicated on this sheet. A copy of this sheet, with the estimated man-hours written on the blank line to the left of the specified items, shall be submitted with the Survey Schedule to the Engineer _____ days prior to the Presurvey Conference - Construction Survey.
- Stakes and Monuments which are damaged or destroyed by the progress of construction shall be replaced by the Contractor at no additional cost to the Department.
- The Contractor shall furnish an As Staked (or 3D Design Modeling Electronic Files) Earthwork Quantity report to the Engineer prior to completion of twenty percent (20%) of the planned earthwork in any phase as per the CDDT Survey Manual. A printed copy of the As Staked (or 3D Design Modeling Electronic Files) Earthwork data report and a computer disk with that information on it, in the specified format shall be submitted to the Engineer. The Contractor shall field verify original ground cross sections at a maximum 500 feet intervals.
- Prior to beginning work on any subsequent operation, such as placing base course or paving, the Contractor shall certify in writing to the Engineer that the final grade is within specified tolerance.
- The Contractor's surveyor shall perform all field surveying and calculations necessary to tie plan grades into field grades.
- The Contractor shall coordinate construction staking on the project with any utility work.
- Fieldbooks shall contain daily records of points set and or measurements observed. The information recorded shall contain: date, crew members' names, point no., description, staking information, and sketches. If the survey information is collected electronically, information recorded shall be provided to the Project Engineer in a hard copy format that is intuitive, clear and related to the supplemental information recorded in the field books. All linear surveys, such as slope stakes and blue tops, shall have the station and offset information related to the measured information. Non-linear surveys such as structures staking shall have sketches relating electronic information, such as point numbers, to the sketch.
- The Contractor's surveyor shall submit the following fieldbooks to the Engineer:
 - Horizontal Control (Primary & Secondary)
 - Vertical Control (i.e. Benchmarks)
 - Property Pin Ties
 - Horizontal Alignment
 - Grading
 - Slope Staking
 - Minor Structures
 - Major Structures
 - One fieldbook for each work category shown on this sheet
 - Other Fieldbook(s): _____
- The Contractor's surveyor shall submit the following (prior to surveying on the project) to the Engineer:
 - All required Instrument Calibrations

Print Date: 20-Dec-22	
File Name: HS_Survey_Tabulation_Sheet.dgn	
Horiz. Scale: 1:1 Vert. Scale: As Noted	
Unit Information Unit Leader Initials	

Sheet Revisions		
Date:	Comments	Init.

Colorado Department of Transportation

Street Address
 XXXXXXXXXXXXXXXXXXXX
 City, State Zip Code
 Phone: XXX-XXX-XXXX FAX: XXX-XXX-XXXX

Region Number or Staff Initials

As Constructed	SURVEY TABULATION SHEET		
No Revisions:	Designer: XXXXXXXX	Structure Numbers	X-XX-XX
Revised:	Detailer: XXXXXXXX		X-XX-XX
Void:	Sheet Subset: XXXXXXXX	Subset Sheets: XXX of XXX	

Project No./Code
Project Number
Code
Sheet Number XXX