

Pre-Approved Product Evaluation Request & Summary

Product Evaluation Coordinator
Colorado Department of Transportation 4670 North Holly Street
Denver, Colorado 80216

APL Reference No.

CD5993-26 Only

Material Code

702.06 CDOT Use Only

Material Code description full name

Sealant Hot poured Type II only

Part 1

Product Name:

CrackMaster Mastic Gray- CPT

Product category:

Sealant (Joint/Crack)\Hot Applied Type II\ Gray for Concrete

Product Representative / Distributer (name & address):

Julia Bitter

P&T Products
472 Industrial Pkwy
Sandusky, OH 44870

Manufacturer (name & address):

P&T Products

P&T Products
472 Industrial Pkwy
Sandusky, OH 44870

Phone: (419) 621-1966 E-mail juliab@pntproducts.com

Website address
pntproducts.com

Phone: (419) 621-1966 E-mail: info@pntproducts.com

Website address
pntproducts.com

Description of the product: (Include specific quantifiable details from the tech data sheet. Advertising generalities are not appropriate.)

CrackMaster Mastic Gray - CPT is a hot-applied repair mastic comprised of a polymer-modified binder and select aggregate. This material is self-adhesive. CrackMaster Mastic Gray - CPT resists cracking, delamination, and spalling. It is a flexible material that can withstand heavy loads, weather, traffic and thermal movement. CrackMaster Mastic Gray - CPT provides a high-friction surface to ensure driver safety. Compaction equipment is not necessary with CrackMaster Mastic Gray- CPT. This repair system is formulated to provide a feathered edge.

Restrictions, (installation and/or use):

CrackMaster Mastic Gray - CPT is recommended for sealing wide cracks and joints, as well as repairing a large variety of distresses in cement and asphalt pavements. It is designed for large cracks and distressed surface areas too small for repaving yet too large for traditional hot-applied crack sealants.

Use of the product, and Benefit to CDOT (be specific to CDOT highway activities only):

CrackMaster Mastic Gray - CPT is recommended for sealing wide cracks and joints, as well as repairing a large variety of distresses in cement and asphalt pavements. It is designed for large cracks and distressed surface areas too small for repaving yet too large for traditional hot-applied crack sealants.

Specifications: (listing those applicable is required.)

<input checked="" type="checkbox"/>	CDOT	702.06
<input type="checkbox"/>	AASHTO	
<input checked="" type="checkbox"/>	ASTM	D 5329
<input checked="" type="checkbox"/>	Other	Attached TDS Specifications
<input type="checkbox"/>	Other	

Certificate of Compliance

Certificate of Verification

Product Testing: (National/independent laboratories or universities with Report Date.) A certified Test Report (CTR) is provided to validate all claims.

<input type="checkbox"/>	AASHTO Product Evaluation & Audit Solutions (NTPEP)	
<input type="checkbox"/>	ASTM	
<input type="checkbox"/>	Other	
<input type="checkbox"/>	Other	
<input type="checkbox"/>	Other	

State DOT Approvals: Missouri

Expiration Date 5 Year Cycle 04/06/2031

Sample Submitted Yes No N/A Safety Data Sheets (SDS): Yes No N/A

Signature is only required if their are CDOT Restrictions as per CDOT Approving Authority

This product is suitable for use on all CDOT Projects requiring crack/joint sealant.

CDOT Use Only

Evaluators Signature:

Vincent Battista Digitally signed by Vincent Battista
Date: 2026.04.06 11:24:13 -06'00'