Areas of Special Attention are locations or stretches along the Interstate 70 (I-70) Mountain Corridor that have been identified as having multiple or unique issues. These areas were identified by stakeholders during the Aesthetic Working Group.

Addressing the various issues and integrating them into design solutions requires further understanding of stakeholder concerns, the issues, and some of the suggested solutions. These concerns, issues, and suggested solutions (when available) have been recorded and provided in a report for each Area of Special Attention.



WHY WOLCOTT CURVES IS AN AREA OF SPECIAL ATTENTION

- Top of Eagle County Plateau
- Tight curves and road geometries
- Proposed AGS
- I-70 improvements

How to Use this Report

The intent of this report is to provide to planners and designers of the I-70 Mountain Corridor a record of the discussions focused on the Wolcott Curves Area of Special Attention. To that end, this report includes the concerns expressed by many stakeholders: citizens, business owners, property owners, organizations, and agencies. This report also includes a description of the area, the goals and objectives for the area, relevant plans that must be reviewed, and the suggested process for moving forward.

This report is not an exhaustive list of alternatives and may not include recent comments and issues.

Issues and Proposed Improvements

The Wolcott Curves Area is located at the top of the Eagle County Plateau and offers dramatic views of the plateau before ascending into the alpine landscape of the Rocky Mountains. The series of curves and road geometries at Wolcott are hazardous to travelers, and safety improvements must be taken into consideration in any future I-70 design in this location. Proposed I-70 Improvements include Advanced Guideway System (AGS) and curve safety improvements.

Area Limits and Description


Important contextual features and places within the Wolcott Curves Area add to its unique character. These include the Eagle County Plateau, Red Sky Ranch, the town of Wolcott, dramatic views, recreation opportunities, ski resorts, and proximity to the Eagle River. The interchange at Wolcott also serves as a regional access point to the Flat Tops Mountain Range via Colorado State Highway 131 (CO 131). The functional aspects of the Wolcott Curves area are graphically represented on the Functional Context Map, which demonstrates an understanding of the layout and operational aspects of the area – including land use, circulation and access interrelationships, and operational priorities.



Wolcott Curves

DRAFT FEBRUARY 2011

East Entrance to Glenwood Springs Functional Context Map



DRAFT FEBRUARY 2011



VIEW TOWARD 1-10 FROM HIGHWAY 131



APPROACHING EXIT 151 FROM THE WEST

VIEW WEST AT WOLCOTT CURVES

VIEW TOWARD I-10 FROM WOLCOTT

VIEW EASTBOUND ENTERING THE WOLCOTT CURVES AREA

WESTERN SLOPE CANYONS

Transportation Vision Elements to Be Considered

Future improvements and studies in the I-70 Mountain Corridor through the Wolcott Curves Area should consider each of the elements outlined below.

- Advanced Guideway System (AGS)
- I-70 Improvements
 - Road Improvements
 - Curve Safety Improvements

Goals and Objectives

- Improve safety through a variety of non-engineering-related enhancements (increased lighting coverage, landslide mitigation, wildlife crossings, etc).
- Evaluate realignment alternatives that will provide safer road geometries.
- Utilize structured and elevated roadway solutions to minimize disturbance on steep slopes and the Eagle River.
- Vertically or horizontally separate eastbound and westbound lanes where possible to reduce glare from oncoming traffic and minimize disturbance.
- Provide for wildlife movement corridors with fencing, overpasses, and/or underpasses.
- Consider realigning or placing utilities underground to remove additional visual distractions in this area.
- Improve the aesthetics and slope stability of existing rock cuts.
- Preserve and restore significant stands of vegetation, especially in riparian areas.
- Improve the consistency in design and color schemes for roadway structures (sound walls, retaining walls, barriers, guardrails, bridges, and wildlife fencing).
- Improve the water quality of the Eagle River and include aesthetic restoration after construction.
- Preserve major site resources and features such as topography, views, unique vegetation, geological features, wetlands, and other qualities native to the site and its surroundings.
- Focus lighting at the major regional transportation (CO 131) interchange (mile 157).
- Mitigate unfavorable visual appearances (i.e., the CDOT maintenance facility) by utilizing landforms and landscaped buffers.

Design and Engineering Guidance

I-70 Mountain Corridor Design Criteria - Overview

The following overarching principles apply to the entire I-70 Mountain Corridor. These principles are supported by the Aesthetic Guidance, which is divided into Design Segments and which presents specific objectives and strategies. The principles are provided to the future managers and designers of transportation facilities within the corridor to guide the desired outcomes of individual projects.

A. Corridor Design Character

Elegantly engineered transportation facilities will reflect function, simplicity, and integrated design throughout the corridor. The landscape under, adjacent to, and beyond the structures supporting transportation facilities shall be rugged, organic, and made of natural materials. Designers will not attempt to make facilities falsely appear natural with the application of materials. The linkage of land and transportation features will be visualized as a single design effort, rendering a cohesive quality to the entire corridor. The geometry of the road should maintain a continuous flow and fit existing land forms.

B. Integrated and Complete Design

All facilities included in a project -- whether primary or auxiliary to the function of the corridor -- will be identified, programmed, and conceptually designed prior to completion of 30% design. This will include consideration of the entire construction disturbance zone. A comprehensive design is necessary in order to plan for all construction disturbances and create an integrated, sustainable corridor that accounts for each project. Aesthetic objectives and functionality are optimized when all elements are included in the design at inception. Integrated design includes considerations such as drainage and hydrology, water quality, wildlife crossings, rock cuts, life cycle costs, and long-term maintenance.

C. Partnerships to Create the Corridor

Corridor design will include consideration of a buffer and transition area between transportation facilities and community-oriented land uses. The landscape planting, earthwork, structural solutions, and location of the transportation facilities need to be fully examined in order to avoid potential visual and scenic impacts, buffer highway noise, and preserve community character and patterns. Road and trail connections and multi-modal travel corridor opportunities should be considered. Reinforcement of alternative methods of travel such as pedestrian and biking paths should be incorporated and coordinated with community and recreational planning efforts.

D. Using the Programmatic Environmental Impact Statement (PEIS)

The I-70 Mountain Corridor PEIS contains critical background and reference information foundational to design. The PEIS should be reviewed throughout the entire design process for insight into the detailed assessments of various corridor aspects. This will ensure alignment and consistency with the analyses and recommendations determined by the PEIS.

E. Corridor-Wide Projects

Projects that will be implemented across the entire corridor have the potential to create elegant consistency. These projects should be approached with an additional level of care and scrutiny, and should address the ideas set forth in the Aesthetic Guidance for all four corridor Design Segments. The goal should be a project that yields an overall aesthetic benefit to the corridor.

Engineering the I-70 Mountain Corridor

Design Criteria

Seven required Engineering Design Criteria have been developed to address the unique characteristics of the I-70 Mountain Corridor. These criteria are intended to influence the alignment of the transportation facilities and are an essential component of the engineering design.

The Engineering Design Criteria have been developed and adopted by the Colorado Department of Transportation (CDOT) because they represent an approach that enhances safety, mobility, and sustainability while reducing maintenance through design and engineering.

Design Criteria Categories

The following Design Criteria categories direct the development of both I-70 and the Advanced Guideway Systems (AGS)*:

- Design Speed
- Alignment
- Slope Cut and Fill
- Disturbance
- Rock Cut
- Bridge Structures
- Sound Attenuation

*As the AGS for the I-70 Mountain Corridor is further defined, developed, and refined, the criteria may be updated to match the chosen technology.

Application of Design Criteria

All of the Design Criteria must be met in Life Cycle Phase 2: Project Planning. Alternatives may be refined in Life Cycle Phase 3: Project Design, when the designer is able to determine which criteria may require an exception and why. The one exception for this requirement is in Areas of Special Attention, where a design exception may be considered in Phase 2 due to the complexity of the issues involved.

Federal, state, and local agencies will neither officially review nor grant design exceptions until Life Cycle Phase 3: Project Design.

Project Leadership Team Role

The Project Leadership Team (PLT) must be apprised of the Design Criteria being used on its I-70 Mountain Corridor project.

Justification for any criteria that would not be met as determined during design must be presented, discussed, and agreed upon by the PLT. Consideration will be given to the I-70 Mountain Corridor Core Values; safety; operation; compatibility with the overall network; character of traffic; cost implications; and impacts to scenic, historic, and environmental features. Other variables to consider include the amount of change to the criteria, its effect on other criteria, and any additional impacts that one change may make.

Design Exception Process

Due to challenges presented within the I-70 Mountain Corridor, a situation may arise in which the existing Design Criteria cannot be met, or in which the impact of meeting the criteria would be too great. Should this be the case, a design exception must be requested. Design exceptions may assist a designer in finding a transportation solution that balances impacts to scenic, historic, and culturally or environmentally sensitive areas while still providing for safety and mobility. Designers should think innovatively, consider the Core Values, and take into account the flexibility available to them when designing a transportation solution for the I-70 Mountain Corridor.

Design exceptions may be granted for the following justifications:

- Complementing surrounding physical characteristics
- Enhancing safety
- Increasing capacity
- Reducing costs
- Protecting the environment
- Preserving historic and scenic elements
- Interfacing with multiple modes of transportation
- Utilitizing new technology or innovative approaches
- Doing the right thing

I-70 Mountain Corridor Design Criteria

WESTERN SLOPE CANYONS

DRAFT FEBRUARY 2011

Design Criteria		Remarks	
Design Speed	For I-70, 65 MPH design speed. For Advanced Guideway System (AGS), dependent on technology.	1) Posted speed of 55 MPH of I-70.	
		2) Federal Highway Administration (FHWA) 1 controlling criteria and Colorado Department of Transportation (CDOT) Design Criteria apply.	
		3) Technology-appropriate Design Criteria will apply to AGS.	
Alignment	Eastbound highway lanes, westbound highway lanes, and the AGS will be designed as separate,	1) Provides a recovery zone.	
		 Median required for snow removal and maintenance. 	
	 independent alignments. The three alignments will maintain no less than the existing median width or create a clear zone that does not require a guardrail or barrier. No loss of existing vertical separation of highway lanes will occur in any section. 	 Separation prevents headlight glare, improving safety and maintenance conditions. 	
		 Separate alignments will adapt to topographic conditions. 	
		5) See Illustration 1 for highway cross section.	
Slope Cut and Fill	Limits of physical disturbance shall be less than 40 vertical feet from the top of the pavement or rail platform to the farthest edge of cut or fill.	 Planting, re-vegetation, an restoration of slopes will b successful with flatter slop embankment. 	
	Cut and fill embankment will not exceed a slope of 2.5:1 (H:V).	 Slopes will be more easily maintained and erosion and sediment transport wi be manageable. 	
	All roadway retaining walls over 12' in height will be installed below the elevation of the roadway.	3) See Illustrations 1 and 2.	

WESTERN SLOPE CANYONS

DRAFT FEBRUARY 2011

Design Criteria		Remarks	
Disturbance	Construction will be fully contained with areas of historic or current disturbance if no centerline change occurs.	 Existing maintenance problems will be resolved or improved by staying within the existing limits of disturbance. 	
	New alignments must be consistent with Design Criteria for slope cut and fill.	 Construct without increasing the disturbance zone. 	
Rock Cut	A geotechnical analysis report will be completed and reviewed prior to any proposal to create rock cuts for an alignment.	 Allows for understanding of rock formations at an early planning stage to potentially avoid rock cuts. 	
	If rock cuts are required, naturalized custom cuts methods are required. Rock cuts shall be constructed using scatter blasting techniques and provide for adequate rockfall area at the base.	Avoids rockfall mesh and reduces maintenance.	
		 Scatter blasting techniques provide a naturalized cut and allow safety from rockfall to be incorporated in the design. 	

WESTERN SLOPE CANYONS

DRAFT FEBRUARY 2011

Design Criteria		Remarks	
Bridge Structures	Bridge structures will not utilize slope paving techniques and will require a closed-end abutment design with a minimum vertical height of 8', measured below the bridge girder. Bridge embankments shall be 2.1:1 maximum.	1)	Avoids the maintenance of slope paving.
		2)	Provides a method of incorporating re-vegetation and landscape into bridge slopes.
		3)	A clear span over streams and drainages avoids water quality construction impacts and reduces maintenance and pier scour.
		4)	Provides benefits below bridges for vehicle clearance, wildlife crossing, solar access, and re- vegetation success.
		5)	See Illustrations 3 and 4.
Sound Attenuation	Sound buffering and attenuation will be designed in conjunction with the horizontal and vertical alignment to eliminate the need for noise mitigation.		Design can minimize or eliminate additional noise mitigation.
	Mitigation, if required, will integrate landforms, landscape planting buffers, and walls.		If sound walls are required, see Illustrations 5 and 6.




ILLUSTRATION 1: DESIGN CRITERIA FOR ALIGNMENT AND CUT AND FILL




ILLUSTRATION 2: DESIGN CRITERIA FOR CUT AND FILL




ILLUSTRATION 3: DESIGN CRITERIA FOR BRIDGE STRUCTURES OVER I-70




ILLUSTRATION 4: DESIGN CRITERIA FOR I-70 BRIDGE OVER NATURAL FEATURES OR OTHER ROADWAYS

WESTERN SLOPE CANYONS

DRAFT FEBRUARY 2011




ILLUSTRATION 5: DESIGN CRITERIA FOR SOUND ATTENUATION




ILLUSTRATION 6: DESIGN CRITERIA FOR SOUND WALL DESIGN

WESTERN SLOPE CANYONS

DRAFT FEBRUARY

2011

Who Should Be Involved?

Stakeholders in the Wolcott Curves Area include citizens, business owners, property owners, organizations, travelers, transporters, and agencies. Future studies, planning, and design work should continue to involve not only these stakeholders, but also planning, design, landscape architecture, operations, environment, public process, and communication experts. This involvement and collaboration will allow the stakeholders to look for common ground and provide opportunities to develop partnerships to further the shared vision.

The following is an initial list of agencies and organizations. Additional stakeholders and partners should be involved as they are identified.

- Community members •
- Town of Wolcott
- Eagle County
- Colorado Department of Transportation
- Federal Highway Administration
- Federal Railroad Administration •
- US Forest Service •
- Colorado Division of Wildlife •
- Colorado Historical Society
- I-70 Coalition •
- Northwest Council of Governments •
- US Army Corps of Engineers •
- US Fish and Wildlife Service •
- Colorado Department of Public Health and Environment •
- Colorado Motor Carriers •
- National Trust for Historic Preservation •
- Audubon Society •
- Colorado Rail Passenger Association •
- OmniTrax •
- **Trout Unlimited** •
- Colorado Preservation Inc. •
- ECO-Resolutions •
- Center for Native Ecosystems
- Colorado Association of Transit Agencies

WESTERN SLOPE CANYONS 2011 DRAFT FEBRUARY

Other Relevant Materials to Be Included in the Process

For all studies along the I-70 Mountain Corridor, a primary source of information must be the Programmatic Environmental Impact Statement (PEIS). The Wolcott Curves Area of Special Attention includes the PEIS elements of the Advanced Guideway System (AGS) and planned highway improvements.